

# Honeywell®

## 1470g Voyager XP handheld omnidirectional barcode reader, 1D, 2D, USB, black, with flexible stand

Honeywell Voyager Extreme Performance (XP) 147x is the next generation of Honeywell handheld sensors, designed for in-store retail environments. The Voyager XP 147x scanner offers highly accurate scan performance, easily capturing damaged and difficult-to-read codes. Scanner corresponds to the new Tobacco Directive - reads DotCode.

With better durability and a more powerful scan capability than previous models the Voyager XP 147x scanner is the perfect option for workflows that include 1D and 2D barcode reading and require a more robust and reliable solution. The scanner's extended scan distance will reach right to the bottom of the cart without bending and wasted time at the checkout. The Voyager XP 147x scanner is fully backwardcompatible with existing Voyager accessories, reducing total cost of ownership.



#### **Key features:**

- more powerful scan capability than previous models
- · easily reads even difficult-to-read and damaged codes
- fully backward-compatible with existing Voyager accessories
- great price/performance ratio
- reads DotCode











### **Technical Description**

#### **Functionality & Operation**

| Functionality & Operation           |   |
|-------------------------------------|---|
| Communication interface             | USB   |
| 1D Barcode Symbologies              | All standard one-dimension barcodes   |
| 2D Code Symbologies                 | DotCode, PDF417, all standard 2D-Codes                                      |
| Optical                             |   |
| Bar code scanner                    | 2D Imager   |
| Depth of scan field                 | 5 - 400 mm  |
| Electrical                          |   |
| Power Source                        | 4.0 ~ 5.5VDC  |
| Mechanical                          |   |
| Color                               | black   |
| Dimensions                          | Width: 62mm, Height: 169mm Length: 82mm                                     |
| Weight                              | 130g  |
| Environment                         |   |
| Ingress protection                  | IP40  |
| Maximal ambient light               | 100000lux   |
| Shock resistance                    | Withstands 30 drops from 1,8 m onto concrete surface, 1000 tumbles at 50 cm |
| Operating humidity (non-condensing) | 0 to 95%  |
| Electrical static discharge         | ±8kV contact, ±15kV air   |
| Storage temperature                 | -40 to 60°C   |
| Operating temperature               | 0 to 50°C   |
| Others                              |   |
| Warranty                            | 5 years   |

CODEWARE, s.r.o. Jaromírova 484/37

120 00 Praha 2 - Nusle IČ: 61061395, DIČ: CZ61061395

+420 222 562 444 codeware@codeware.cz https://www.codeware.cz/



