

Honeywell®

Granit XP 1990iSR - industrial-grade Area-Imaging scanner, DPM, USB

Act fast, the price is valid only until the stock is sold out! The Granit™ XP 1990iSR model offers high-durability, extreme performance scanning for standard range operations.

With an unmatched range and the option of wireless freedom, Granit scanners maximize operator productivity in the harshest environments.



Key features:

- high-durability
- the custom built IP67-rated housing is able to withstand 7,000 3.3′ (1 m) tumbles and survive 50 drops from 10′ (3 m)
- provides extreme performance scanning, even on damaged and low-quality barcode
- s reads DPM cod

es

Honeywell Granit Durability

Test YOUTUBE='kgnqVAz









Technical Description

Functionality & Operation

| Functionality & Operation | |
|-------------------------------------|---|
| Indicators | beeper, vibration, Good Decode LEDs |
| Communication interface | USB |
| 1D Barcode Symbologies | All standard one-dimension barcodes, Digimarc |
| 2D Code Symbologies | DotCode, all standard 2D-Codes, OCR |
| Optical | |
| Minimum symbol contrast | 20% |
| Bar code scanner | 2D Imager (1280 x 800 px) |
| Depth of scan field | 0 - 837 mm |
| Electrical | |
| Power Source | 4.0 VDC - 5.5 VDC |
| Power Consumption - Standby | 0.5W (100 mA @ 5VDC) |
| Power Consumption - Operation | 2.35W (470 mA @ 5 VDC) |
| Mechanical | |
| Dimensions | Width: 100mm, Height: 76mm Length: 192mm |
| Weight | 320g |
| Environment | |
| Operating temperature | -30 to 50°C |
| Storage temperature | -40 to 70°C |
| Operating humidity (non-condensing) | 0 to 95% |
| Ingress protection | IP67 |
| Shock resistance | 7000 tumbles at 1m , Withstands 50 drops from 3 m onto concrete surface |
| Maximal ambient light | 100000lux |
| Electrical static discharge | ±20kV air, ±8kV contact |
| Others | |
| Warranty | 3 years |

CODEWARE, s.r.o. Jaromírova 484/37 120 00 Praha 2 - Nusle IČ: 61061395, DIČ: CZ61061395

+420 222 562 444 codeware@codeware.cz https://www.codeware.cz/



