



## CipherLab 1500P RS232: CCD scanner, black + RS232 cable

Fast and ergonomically advanced compact barcode scanner with auto-sense 3in1 stand.

CipherLab 1500 barcode scanner (linear imager) raises the standard of performance, style and affordability. An incredibly comfortable design and the innovative three-way stand makes it easy to use all day long. A large LED and the adjustable tone ensure instant scan recognition that speeds up the workflow. No moving parts and CipherLabs reputation for reliability mean ultra-low maintenance, giving you remarkably low total cost of ownership. And a five-year warranty gaurantees years of worry-free service. The CipherLab 1500 delivers where reliability, durability, comfort, speed, safety, and value matter.



You can easily configure the 1500 scanner with the ScanMaster software.

Bar code scanner CipherLab 1500 is available also in special design for health institutions, pharmacies, and similar social institutes. The housing is cast from a mixture of antibacterial solution developed for this purpose by [Microban](#) corporation.

### Autosense, 3-in-1 stand

Autosense  
Desktop  
Wall mount

### Referential customers

Ministry Of Labor And Social Affairs, Czech (hundreds of scanners)  
Gesto Computers, spol. s r.o., Czech



# Technical Description

## Functionality & Operation

Communication interface	USB, USB-HID, USB-VCP, RS232
1D Barcode Symbolologies	Codabar, Code 128, Code 39, Code 93, EAN 13/UPCA, EAN 8, French Pharma Code, Industrial 2 of 5, Interleaved 2 of 5, Italy Pharma Code, Matrix 2 of 5, MSI, Plessey, Telepen, UPCE, and others
Configuration	by programming barcodes, ScanMaster utility
Programmable features	Data editing, interface selection, symbology, configuration

## Optical

Light source	visible red LED 625nm
Depth of scan field	40-400 mm
Scanning rate	520scan/s
Resolution	3 mil
Maximal skew angle	70°
Maximal pitch angle	70°
Bar code scanner	CCD 2500 px
Minimal PCS value	30%

## Electrical

Power Consumption - Standby	350mA
Power Consumption - Operation	170mA, max. 250 mA

## Mechanical

Weight	145g
Color	black

## Environment

Operating temperature	0 to 50°C
Storage temperature	-20 to 60°C
Maximal ambient light	100000lux
Shock resistance	drop from 1,5 m onto concrete surface
Storage humidity (non-condensing)	5 to 95%
Operating humidity (non-condensing)	10 to 90%
Electrical static discharge	±8kV contact, ±15kV air
Ingress protection	IP30

**CODEWARE, s.r.o.**  
Jaromirova 484/37  
120 00 Praha 2 - Nusle  
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444  
+420 737 274 952  
codeware@codeware.cz  
<https://eshop.codeware.cz/>

