



## 1502 Kit USB: Laser Bar Code Reader with stand, black, USB-HID

Fast and ergonomically advanced compact laser barcode scanner with optional 3in1 stand.

Lightweight and ergonomic, this laser scanner enables workers to capture critical data from 2 to 57 cm away quickly, accurately, and comfortably shift after shift in any work environment.



Together with its build test-proven to survive 1.2 m drops onto concrete the 1502 makes one reliable and valuable choice for laser scanning.

### Main Highlights Of CipherLab 1502 Laser Bar Code Scanner

able to read barcode from 2 to 57 cm (0.8 to 22.4 in.) away

lightweight, ergonomic design for repetitive use

innovative 3-in-1 handsfree scanning, desktop, or wall mount stand for easy scanning

test-proven to withstand 1.2 m (3.9 ft.) multiple drops from concrete

supports multiple languages and symbologies for worldwide applications

widely programmable ScanMaster software included free with purchase for data editing support, interface selection, and symbology configuration

### Innovative 3 in 1 Stand

Handsfree scanning

Desktop holder

Wallmount type



# Technical Description

## Functionality & Operation

1D Barcode Symbolologies	Codabar, Code 128, Code 39, Code 93, EAN 13/UPCA, EAN 13/UPCA + ADDON 2, EAN 13/UPCA + ADDON 5, EAN 8, EAN 8 + ADDON 2, EAN 8 + ADDON 5, French Pharma Code, GS1 Data Bar (RSS), Industrial 2 of 5, Interleaved 2 of 5, Italy Pharma Code, Matrix 2 of 5, MSI, Plessey, Telepen, UCC/EAN-128, UPCA, UPCA + ADDON 2, UPCA + ADDON 5, UPCE, UPCE + ADDON 2, UPCE + ADDON 5
Programmable features	Data editing, interface selection, symbology, configuration
Configuration	by programming barcodes, ScanMaster utility
Language support	Belgian, French, German, Italian, Japanese, Norwegian, Portuguese, Spanish, Swedish, US and UK English, Turkish

## Optical

Light source	visible laser diode VLD 650 nm
Bar code scanner	Laser
Resolution	4 mil
Depth of scan field	20-570 mm
Maximal pitch angle	65°
Maximal skew angle	50°
Scanning rate	100scan/s

## Electrical

Power Source	+5V ±10%
Power Consumption - Standby	35mA
Power Consumption - Operation	210mA

## Mechanical

Dimensions	Width: 153cm, Height: 61cm Length: 93cm
Weight	149g
Color	black

## Environment

Maximal ambient light	100000lux
Operating temperature	0 to 50°C
Storage temperature	-20 to 60°C
Operating humidity (non-condensing)	10 to 90%
Storage humidity (non-condensing)	5 to 95%

### CODEWARE, s.r.o.

Jaromírova 484/37  
120 00 Praha 2 - Nusle  
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444  
codeware@codeware.cz  
<https://www.codeware.cz/>

