



1564A Wireless 2D-code scanner + Cradle + RS232 Cable, Bluetooth

1564 series wireless BT 2D code scanners raise the bar for performance, value and user satisfaction with a 90-meter range, sleek ergonomics and a smart communication stand that serves seven scanners.

An incredibly comfortable design and the innovative three-way stand make it easy to use all day long.No moving parts and CipherLabs reputation for reliability mean ultra-low maintenance, giving you remarkably low total cost of ownership.



You can easily configure the 1564 scanner with the ScanMaster software.

Scanning options:

- trigger
- Auto-sense
- continuous mode
- presentation mode

Adjustable stand:

- desk stand
- wall mount
- auto-sense stan



















Technical Description

Functionality & Operation

Functionality & Operation	
Programmable features	Data editing, interface selection, symbology, configuration
Bluetooth profiles	HID, SPP
Language support	French, German, Italian, Norwegian, Portuguese, Spanish, Swedish, US and UK English, Belgian
Signal coverage	90m
1D Barcode Symbologies	Codabar, Code 128, Code 39, Code 93, EAN 13/UPCA, French Pharma Code, Industrial 2 of 5, Interleaved 2 of 5, Matrix 2 of 5, MSI
2D Code Symbologies	all standard 2D-Codes
Communication interface	Bluetooth® Class 2 (2.4 GHz)Version 4.0+EDR
Configuration	internet guide, by programming barcodes
Optical	
Minimal PCS value	30%
Resolution	3 mil 1D, 5 mil 2D
Maximal skew angle	60°
Maximal pitch angle	60°
Depth of scan field	28-305 mm
Scanning rate	60scan/s
Bar code scanner	2D Imager
Electrical	
Power Source	+5V ±10%
Power Consumption - Standby	22mA
Power Consumption - Operation	166mA
Main battery pack operating time	26hod
Mechanical	
Color	black
Weight	185g
Environment	
Ingress protection	IP30
Maximal ambient light	100000lux

Chack resistance

dran from 1.2 m anto concrete curface



120 00 Praha 2 - Nusle IČ: 61061395, DIČ: CZ61061395

+420 222 562 444 codeware@codeware.cz https://www.codeware.cz/



