

CipherLab BT-1661 CCD Scanner+Battery, Bluetooth, rechargeable

Single line CCD scanner, rechargeable, thanks Bluetooth it can be attached to mobile phone, PDAs etc.

Available Models



- 1660 - powered by two alkaline batteries of AAA size
- 1661 - rechargeable model with Li-ION accumulator
- 1661H - with antimicrobial housing, suitable for healthcare

Key features:

- a built-in Bluetooth for instant connections, anywhere, any time
- 100 scans/second scanning rate for fast, accurate workflow
- a lightweight, ergonomic design for repetitive use
- D.O.F. 3.5 to 38 cm, resolution 3 mil, minimum 30% PCS
- Line of sight coverage up to 10 meters or 33 feet
- Supports multiple languages and symbologies for worldwide applications
- Low power consumption
- Includes free ScanMaster software

Pocket bar code collector CipherLab 1661 is available also in special design for health institutions, pharmacies, and similar social institutes. The housing is cast from a mixture of antimicrobial solution developed for this purpose by Microban corporation



Technical Description

| Functionality & Operation | |
|-------------------------------|---|
| 1D Barcode Symbolologies | Codabar, Code 128, Code 39, Code 93, French Pharma Code, GS1 Data Bar (RSS), Industrial 2 of 5, Interleaved 2 of 5, Italy Pharma Code, Matrix 2 of 5, MSI, Plessey, Telepen, UPCE, and others |
| Configuration | ScanMaster utility, by programming barcodes, by Bluetooth |
| Programmable features | Symbology configuration, data editing |
| Memory | 256Kb |
| Operation interface | 2x button |
| Wireless communication | Bluetooth® |
| Language support | US and UK English, French, Nederland, Norwegian, Italian, Swedish, Spanish, German, Portuguese |
| Signal coverage | 10m |
| Bluetooth profiles | SPP, HID |
| WPAN Features | Bluetooth® Class II v3.0 2.4 GHz |
| Optical | |
| Light source | visible red LED 650 nm |
| Resolution | 3 mil |
| Maximal skew angle | 70° |
| Maximal pitch angle | 70° |
| Bar code scanner | CCD 2500 px |
| Minimal PCS value | 30% |
| Electrical | |
| Power Source | 2x AAA alkaline baterie, Rechargeable Li-Ion Battery |
| Power Consumption - Standby | 15mA |
| Power Consumption - Operation | 150mA |
| Mechanical | |
| Dimensions | Width: 95mm, Height: 35mm, Length: 20mm |
| Weight | 50g including battery |
| Color | dark grey, white |
| Environment | |
| Operating temperature | 0 to 50°C |
| Storage temperature | 20 to 60°C |

CODEWARE, s.r.o.
Jaromirova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
+420 737 274 952
codeware@codeware.cz
<https://eshop.codeware.cz/>

