

CipherLab BT-1661H CCD Barcode Memory Scanner, Bluetooth, rechargeable, healthcare design

Single line CCD scanner, rechargeable, thanks Bluetooth it can be attached to mobile phone, PDAs etc. Antimicrobial design for healthcare.

Available Models



- 1660 - powered by two alkaline batteries of AAA size
- 1661 - rechargeable model with Li-ION accumulator
- 1661H - with antimicrobial housing, suitable for healthcare

Key features:

- a built-in Bluetooth for instant connections, anywhere, any time
- 100 scans/second scanning rate for fast, accurate workflow
- a lightweight, ergonomic design for repetitive use
- D.O.F. 3.5 to 38 cm, resolution 3 mil, minimum 30% PCS
- Line of sight coverage up to 10 meters or 33 feet
- Supports multiple languages and symbologies for worldwide applications
- Low power consumption
- Includes free ScanMaster software

Pocket bar code collector CipherLab 1661 is available also in special design for health institutions, pharmacies, and similar social institutes. The housing is cast from a mixture of antimicrobial solution developed for this purpose by Microban corporation



Technical Description

Functionality & Operation	
1D Barcode Symbolologies	Codabar, Code 128, Code 39, Code 93, French Pharma Code, GS1 Data Bar (RSS), Industrial 2 of 5, Interleaved 2 of 5, Italy Pharma Code, Matrix 2 of 5, MSI, Plessey, Telepen, UPCE, and others
Configuration	ScanMaster utility, by programming barcodes, by Bluetooth
Programmable features	Symbology configuration, data editing
Memory	256Kb
Operation interface	2x button
Wireless communication	Bluetooth®
Language support	US and UK English, French, Nederland, Norwegian, Italian, Swedish, Spanish, German, Portuguese
Signal coverage	10m
Bluetooth profiles	SPP, HID
WPAN Features	Bluetooth® Class II v3.0 2.4 GHz
Optical	
Light source	visible red LED 650 nm
Resolution	3 mil
Maximal skew angle	70°
Maximal pitch angle	70°
Bar code scanner	CCD 2500 px
Minimal PCS value	30%
Electrical	
Power Source	2x AAA alkaline baterie, Rechargeable Li-Ion Battery
Power Consumption - Standby	15mA
Power Consumption - Operation	150mA
Mechanical	
Dimensions	Width: 95mm, Height: 35mm, Length: 20mm
Weight	50g including battery
Color	dark grey, white
Environment	
Operating temperature	0 to 50°C
Storage temperature	20 to 60°C

CODEWARE, s.r.o.
Jaromirova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
+420 737 274 952
codeware@codeware.cz
<https://eshop.codeware.cz/>

