

CPT-8600C Mobile Terminal, CCD, 8MB, 29 kl.

The 8600 series mobile computer is a pioneer product of new generation. It is a combination of functionality, ruggedness, and mobility rolled all into one efficient device. The new 8600 has a color display that defines background and text with various colors to improve readability and support rich data management tasks. It runs on CipherLab OS to reduce redundancy in programs and applications for users.

The modular charging / communication system and swappable keypad gives user flexible configuration into his hands. The 8600 series mobile computer is specifically designed with top durability in mind. Being compact and ergonomic, it's extremely rugged with IP65 standard which is capable of enduring exposure to dust, dirt and water jets. The protection features make the 8600 series one of the toughest of its kind in the market. The 8600 series' rugged features also have the optional hard shell that gives extra protection and ease of grip. The LCD display is covered by a polycarbonate panel protector for extra protection from hits and accidents.



The 8600 series is purposely designed with ergonomics and lightweight to provide more flexible mobility for its users. Weighing only approximately 240 grams, it allows for comfortable operation all-day with maximum mobility. It also has an optional pistol-grip that the users can employ for easier operation of intensive scanning to improve productivity. The 8600 series also comes with GPS as an option which is unique among other products of its kind. When it is required, this GPS feature can be engaged to improve accuracy of outdoor asset management and give field workers the ability to provide more complete information for management anywhere.

The most significant features of CipherLab CPT-8600 mobile terminal

- color LCD display with polycarbonate panel protector;
- swappable keyboard;
- optional RFID reader;
- optional GPS module;
- optional handle;
- modular design of the accessories;

- wireless capabilities of Bluetooth 4.0 and 802.11 b/g/n at 8630 and 8660 models;
- strong ruggedness and IP65 ingress protection.



Technical Description

Functionality & Operation

1D Barcode Symbolologies	All standard one-dimension barcodes
Operating system	proprietary
Communication interface	USB, keyboard
Data memory	8MB DRAM
Keyboard	numeric, 29 keys, with programmable LED backlight
Display type	2,83" TFT LCD color with programmable LED backlight
Data retention	25den
Indicators	2x LED (dual-color, red/green and blue/green), vibration, speaker
Expansion slot	Micro SD Card (SDHC)
Program memory	16MB Flash
CPU Type	ARM Cortex-M3

Optical

Bar code scanner	CCD
Resolution	320x240 px

Electrical

Main battery pack	Rechargeable Li-Ion battery 2200 mAh, 3,7V, Rechargeable Li-Ion battery 1100 mAh, 3,7V
Main battery pack operating time	64hod 2200 mAh, 32hod 1100 mAh

Mechanical

Dimensions	Width: 30mm, Height: 60mm Length: 170mm
Weight	240g including battery

Environment

Electrical static discharge	±8kV contact, ±15kV air
Ingress protection	IP65
Shock resistance	1000 tumbles at 1 m, Withstands multiple drops from 1,8 m to concrete, in all axis and in operating temperature range
Storage humidity (non-condensing)	5 to 95%
Operating humidity (non-condensing)	10 to 90%
Storage temperature	-20 to 70°C
Operating temperature	10 to 50°C

CODEWARE, s.r.o.

Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
<https://www.codeware.cz/>

