

Honeywell®

Datamax A Class Mark II industrial barcode printer into production lines, RH, 300dpi, LCD displej, TT,DT, USB,Serial,LAN

The A-Class Mark II family of advanced print engines is designed for high-demand multi-shift applications requiring fast throughput and proven reliability. It includes a number of innovative design features such as stainless steel hardware components, a modular design for enhanced serviceability, coated side in/coated side out thermal transfer ribbon assembly, a full graphics display, intuitive menu navigation, and an optional remote display.

The A-Class Mark II is a superior print engine used in high demand print and apply applications offering the highest level of performance and reliability. Known in the industry for its unique stainless steel cover, the A-Class is ideal for the specialized needs of harsh or corrosive environments. The state of the art modular design offers easy on-demand serviceability that significantly reduces down time of the demanding multi-shift mission critical applications. The industry standard mounting and intuitive menu navigation makes the A-Class the print engine of choice for automated print and apply applications.



Key features of the printer Datamax A Class Mark II:

- A stainless-steel cabinet protects your printer for years of service in rugged and extreme environments
- Expanded connectivity includes four types of communication ports as standard features - 10/100 LAN, USB, Serial and Parallel.
- Seamlessly integrates into most existing solutions using PL-Z and PL-I language emulation without changing code
- A large graphic display enables easy navigation, advanced setups and simple operator use.
- Fully integrated UHF RFID solutions available



Technical Description

Functionality & Operation

| | |
|--------------------------|-------------------------------------|
| Print resolution | 300dpi |
| Maximal print width | 168mm |
| Print speed | 304mm/sec (12 ips) |
| Print mode | thermal-transfer |
| Memory | 16MB DRAM 8 MB Flash |
| 1D Barcode Symbologies | All standard one-dimension barcodes |
| 2D Code Symbologies | all standard 2D-Codes |
| Fonts & barcode rotation | 0°, 90°, 180°, 270° |
| Maximal print length | 2540mm |
| Communication interface | RS232, Ethernet, GPIO, USB |

Mechanical

| | |
|------------|---|
| Dimensions | Width: 266mm, Height: 246mm Length: 390mm |
| Weight | 15.3kg |

Consumables

| | |
|----------------------|----------------|
| Ribbon core diameter | 25.4mm |
| Max. ribbon length | 650m |
| Media thickness | 0.06 to 0.25mm |

Environment

| | |
|-------------------------------------|-------------|
| Operating temperature | 4 to 38°C |
| Operating humidity (non-condensing) | 10 to 90% |
| Storage humidity (non-condensing) | 5 to 95% |
| Storage temperature | -40 to 60°C |

Others

| | |
|----------|--------|
| Warranty | 1 year |
|----------|--------|

CODEWARE, s.r.o.
Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
<https://www.codeware.cz/>

