



BD-388III Corded long range CCD

The enhanced linear imager bar code scanner BD-388III offers laser-like and high performance barcode reading: 500 scans/second, 400mm scanning distance for all of barcode reading including EAN 128 code and GS1 data bar.

BD-388III is built with Keyboard, RS232 USB and Wand interface. It supports use replaceable interface cable by RJ45 phone jack; different interface can be interchangeable just by changing cable. It is simplified installation and integration and good to lessen your inventory load.



The scanner is enhanced with Auto Sensor function for hand-free operation to lengthen the optical life. Furthermore, the ergonomic and gun type design body offers maximum comfort for every day use.













Technical Description

Functionality & Operation

nmunication interface USI	
	В
Barcode Symbologies All	standard one-dimension barcodes
ical	
nning rate 500	0scan/s
code scanner CCI	D
trical	
ver Source +5	VDC ±5%
chanical	
y housing AB:	S plastic with rubber
ght 130	0g
nensions Wid	dth: 90mm, Height: 193mm Length: 85mm
ironment	
kimal ambient light 100	000lux
erating temperature 0 to	o 50°C
rage temperature -20	0 to 70°C
erating humidity (non-condensing) 20	to 95%
ck resistance dro	op from 1,2 m onto concrete surface
ers	

CODEWARE, s.r.o. Jaromírova 484/37

120 00 Praha 2 - Nusle IČ: 61061395, DIČ: CZ61061395





