

BP-X21 POS Receipt Printer, space saving, 90 mm/sec, USB, black

Surprisingly small thermal receipt printer. It can be used wherever the most important factor is the minimum space occupied by the device. It is the smallest, lightest, the most price effective, nevertheless with the same drivers and control like all other cash register printers.



YOUTUBE='NjwsHY2SdTA'



Technical Description

Functionality & Operation

Communication interface	RS232, OPOS, JPOS, RJ-11 cash drawer port, USB
1D Barcode Symbolologies	EAN 128, EAN 13, EAN 13/UPCA, EAN 13/UPCA + ADDON 2, EAN 13/UPCA + ADDON 5, EAN 8, EAN 8 + ADDON 2, EAN 8 + ADDON 5, EAN-UCC, Code 128, Code 128 subset A.B.C., Code 39, Code 93, Code128UCC, Codabar, Interleaved 2 of 5, UPCA, UPCA + ADDON 2, UPCA + ADDON 5, UPCE, UPCE + ADDON 2, UPCE + ADDON 5, UPC/EAN, UPC, UPC/EAN/JAN, UPC2, UPC5, ITF-14
2D Code Symbolologies	QR code
Print speed	90mm/sec
Maximal print width	57.5mm
Print mode	direct thermal
Fonts	Font A: 12x24 dots; Font B: 9x17 dots; Cinese: 24x24 dots
Memory	64kB NV flash
Input buffer	32kB
Print resolution	203dpi

Electrical

Power Source	12 VDC
--------------	--------

Mechanical

Dimensions	Width: 114mm, Height: 92.5mm Length: 150mm
Weight	0.41kg
Color	black

Consumables

Maximal roll diameter	60mm
Paper thickness	0.06 to 0.08mm

Environment

Operating temperature	0 to 45°C
Operating humidity (non-condensing)	10 to 80%
Storage temperature	-10 to 60°C
Storage humidity (non-condensing)	10 to 90%

CODEWARE, s.r.o.

Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
<https://www.codeware.cz/>

