



CP-Q3 POS Receipt Printer with autocutter, USB + RS232 + LAN, black

Birch CP-Q3 is the ideal desktop printer for POS kits, include these with iOS operating system. The model with the extended Bluetooth communication interface suitable for tablet solutions. The ideal combination of high quality and reliability at a great price, which is perfectly applicable in any retail environment and certainly find its fans among customers.

Birch Printer CP-Q3 is due to the widespread communication interface 3-in-1 (RS232, USB, Bluetooth or Ethernet, RJ11) suitable for any operation, but most suited to the retail industry. This means not only the conventional shops but especially hospitality such as bars, restaurants, kitchens with orders and other workplaces where required cash register. The printer is equipped with automatic cutter.



Key features of POS printers BIRCH CP-Q3:

- interface: RS232 + USB + Bluetooth or Ethernet + RJ11
- print in Czech
- suitable for POS, particularly for tablet solutions
- can be connected to iOS operating system through AirPrint interface
- ideal for retail- hospitality, bars, restaurants
- · user's friendly
- print speed of 260 mm/s
- print resolution 203 DPI
- ESC/POS commands set compatible
- print all 1D and 2D bar codes and receipts
- resistant cover
- small table dimensions
- automatic cutter
- good price





















Technical Description

Functionality & Operation

| Functionality & Operation | |
|-------------------------------------|---|
| Memory | 4MB |
| Print speed | 260mm/sec (10 ips) |
| 1D Barcode Symbologies | Code 39, EAN 13/UPCA, EAN 8, Code 93, Code 128, Codabar |
| 2D Code Symbologies | QR code, PDF417 |
| Print resolution | 203dpi |
| Input buffer | 2MB |
| Indicators | programmable buzzer for Head Open/Paper End/Print Complete |
| Fonts | 13 international character set, Big5 / GB123 |
| Commands set | ESC/POS |
| Communication interface | RS232, Ethernet, USB-HID, USB-VCP, RJ-11 cash drawer port, OPOS |
| Maximal print width | 82.5mm (±0,5 mm) |
| Print mode | direct thermal |
| Optical | |
| Sensors | open print-head detector, end-of-media detector |
| Electrical | |
| Power Source | 12 VDC ~ 24 VDC |
| Mechanical | |
| Dimensions | Width: 143.5mm, Height: 135mm Length: 183mm |
| Weight | 3.5kg |
| Color | black |
| Consumables | |
| Media thickness | 0.06 to 0.08mm |
| Media type | roll of thermal paper, black-marked media |
| Maximal roll diameter | 83mm |
| Maximal paper width | 82.5mm (±0,5 mm) |
| Environment | |
| Operating temperature | 0 to 45°C |
| Operating humidity (non-condensing) | 10 to 80% |

CODEWARE, s.r.o. Jaromírova 484/37

120 00 Praha 2 - Nusle IČ: 61061395, DIČ: CZ61061395

+420 222 562 444 codeware@codeware.cz https://www.codeware.cz/



