



## CP60 Robust EDA, CE 6.0 R3, Laser, BT, Wi-Fi, GPS, IP67, QVGA, Camera, numeric kbd

The rugged CipherLab CP60 series is an industrial mobile computer designed to fully assist your staff in the field with the most cutting edge specifications. Crafted for the harsh environments of transportation & logistics, warehousing, manufacturing and field service, this tough mobile computer will allow your workers to maximize productivity with the most up-to-date technologies.

Designed specifically for applications in transportation and logistics, warehousing, manufacturing and field service, the CP60 series is rated with IP65/IP67 standards and can withstand 2.4m drops onto concrete, which safeguards its productivity in harsh environments. Along with a powerful 1 GHz processor, CP60 provides operating system options and speeds up all calculations and data input process. CP60 is armed with the most flexible wireless communication options in the forms of 3.8G HSPA+, 802.11 a/b/g/n, and Bluetooth® V2.1. With the rise of 4G technology, CP60 is also ready to provide 4G LTE option. Having GPS / AGPS gives you the power to locate your staff and never get lost. Its on-board 4 GB flash memory coupled with 512 MB SDRAM, allows workers to store more data and run more software at maximum speed. Additionally, the 5 megapixel autofocus camera and versatile reader options give you dependable data under a vast variety of conditions.



#### Main Features of CipherLab CP60

- industrial rate of ingress protection: IP67
- selectable type of bar code scanner: laser, long range laser, 2D imager
- fast 1 GHz processor and large 512 MB / 4 GB memory
- rich with wireless capabilities: 3.8G HSPA+, 802.11 a/b/g/n, Bluetooth® V2.1, GPS
- 5 megapixel autofocus camera

#### Promotional video:

YOUTUBE='7SseSnT2dCQ'



























# **Technical Description**

### Functionality & Operation

Development tools

| Functionality & Operation           |  |
|-------------------------------------|--|
| Display type                        | 3,5" QVGA TFT Transflective LED  |
| Operating system                    | Windows® CE  |
| Keyboard                            | numeric, with LED backlight  |
| 1D Barcode Symbologies              | All standard one-dimension barcodes  |
| 2D Code Symbologies                 | all standard 2D-Codes  |
| Memory                              | 4GB Flash  |
| Memory                              | 512MB DRAM   |
| Expansion slot                      | Micro SD Card (SDHC)   |
| Indicators                          | Three color LEDs, vibration, speaker   |
| Communication interface             | USB, RS232   |
| WWAN Features                       | GSM/GPRS/EDGE: Quad band 850 / 900 / 1800 / 1900 MHz   |
| WLAN Features                       | IEEE 802.11 a/b/g/n, WLAN security: WEP, WPA: PSK, TKIP, WPA2: AES, PSK, WPA-1x: TKIP, EAP-TLS, PEAP, WPA2-1x: AES, EAP-TLS, PEAP, 802.1x: EAP-TLS, PEAP   |
| WPAN Features                       | Bluetooth® Class II v2.1 EDR   |
| Bluetooth profiles                  | A2DP, AOB, AVRCP, DUN, FTP, GOEP, GAP, SDP, SPP, OPP, HID, PAN, HSP  |
| GPS navigation                      | a-GPS  |
| Wireless communication              | GSM, GPRS, EDGE, HSDPA, HSPA+, HSUPA, LTE, WCDMA   |
| Optical                             |  |
| Bar code scanner                    | Laser  |
| Camera                              | 5 MPix, with Autofocus, with LED flash   |
| Electrical                          |  |
| Main battery pack                   | Li-Ion 3600 mAh, 3,7V  |
| Power Source                        | Rechargeable Li-Ion Battery  |
| Main battery pack operating time    | 10hod  |
| Mechanical                          |  |
| Weight                              | 516g   |
| Environment                         |  |
| Storage temperature                 | -30 to 70°C  |
| Operating temperature               | -20 to 50°C  |
| Operating humidity (non-condensing) | 10 to 90%  |
| Ingress protection                  | IP67   |
| Storage humidity (non-condensing)   | 5 to 95%   |
| Shock resistance                    | 2000 tumbles at 1 m, multiply drops from 2,4 m onto concrete surface, 5 drops on each side   |
| Electrical static discharge         | ±8kV contact, ±15kV air  |
| Others                              |  |
| Certifications                      | BSMI, CB, CCC, CE, FCC, MII, NCC, SRRC   |
| D 1                                 | CLULIC CONNET CON CONTROL CONT |

Cipherlab C++/.NET, SDK to support Microsoft® Visual studio 2005, Microsoft® Visual Studio 2008

Recommended software

App-Lock, Kalipso Mobile Application Generator, Naurtech CETerm, SOTI MobiControl (remote devices control), Wavelink Avalanche, Wavelink Terminal Emulators, Backup Utility, Button Assignment, GPS Viewer, Push-to-talk, Signature Capture, CipherLab SmartShell, CipherLab MIRROR Browser, Codeware MOBILE OPERATOR, Codeware MOBILE SALE, Codeware MOBILE STORE, Codeware MOBILE ASSET

Optional accessories

battery charger, belt holster, charging and communication cradle, pistol grip, protective cover

CODEWARE, s.r.o. Jaromírova 484/37 120 00 Praha 2 - Nusle IČ: 61061395, DIČ: CZ61061395

+420 222 562 444 codeware@codeware.cz https://www.codeware.cz/



