

ELATEC

RFID Systems

RFID Reader TWN4 125kHz, USB

The TWN4 MultiTech 2 LF reader/writer allows users to read and write to almost any 125 kHz and 134.2 kHz tags and/or labels. It supports all major transponder technologies like HID, HITAG, Nexwatch, KERI, Cotag, CASI-RUSCO etc.

The reader provides a powerful API which enables system integrators and solution providers to develop complex applications which can be run directly on the reader.



Key features:

- Powerful SDK for writing Apps which are executed directly on the reader
- Firmware update in the field possible
- Onboard 18 kB flash storage, e.g. for storing user accessible non-volatile data
- Direct chip-commands support
- CCID and PC/SC 2.01
- 3D construction data (STEP) available on request



Technical Description

Functionality & Operation

Frequency	125 kHz
Communication interface	USB
Antennas, Antenna inputs	integrated RFID antenna
Reading/writing distance	10cm

Electrical

Power Source	4,3 V - 5,5 V
--------------	---------------

Mechanical

Color	black
Body housing	ABS plastic
Dimensions	Width: 56mm, Height: 18mm Length: 88mm
Weight	116g

Environment

Operating temperature	-25 to 70°C
Relative humidity (non-condensing)	5 to 95%
Storage temperature	-45 to 75°C

Others

Certifications	RoHS-II compliant, CE, FCC, IC, ACA, ACMA
----------------	---

CODEWARE, s.r.o.
Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
<https://www.codeware.cz/>

