

# Honeywell®

## Vuquest 3320g, 1D and 2D barcode scanner, HD, Multi IF, ivory

The Honeywell Vuquest™ 3320g compact area-imaging scanner offers aggressive scanning of all 1D, PDF and 2D barcodes in a lightweight, durable and portable form factor. The scanner's sleek and elegant design also blends seamlessly in retail environments.

The modern and compact Vuquest 3320g area-imaging scanner provides superior-performance scanning of all printed barcodes, and digital barcodes on any smart device. Aggressive reading of barcodes on highly reflective surfaces, such as mobile phone screens, eliminates the need to purchase additional specialty hardware. Powered by Adaptus™ Imaging Technology 6.0, the Vuquest 3320g scanner delivers superior barcode scanning and digital image capture. The TotalFreedom™ 2.0 second generation development platform expands scanner functionality by allowing decoding and formatting plug-ins to be loaded directly onto the Vuquest 3320g scanner, enabling enterprises to rapidly support proprietary or newly developed symbologies.



#### Key features:

- Aggressive Pass-Through Scanning
- A wide array of reading especially when applied to a wide reading and OCR codes at close range
- Screen readers reads codes directly from a computer screen or mobile phone
- Adaptus™ Imaging Technology



















### **Technical Description**

#### **Functionality & Operation**

Functionality & Operation	
Communication interface	Multi-interface - RS232/KBW/USB
1D Barcode Symbologies	All standard one-dimension barcodes
2D Code Symbologies	all standard 2D-Codes
Optical	
Depth of scan field	18 -201 mm
Minimal PCS value	20%
Maximal skew angle	65°
Maximal pitch angle	45°
Bar code scanner	2D Imager
Focal plane	127mm
Electrical	
Power Source	5 VDC ± 0.25V
Power Consumption - Standby	90mA
Power Consumption - Operation	450mA
Mechanical	
Dimensions	Width: 73mm, Height: 51mm Length: 26mm
Weight	77g
Environment	
Operating temperature	0 to 40°C
Storage temperature	-20 to 70°C
Operating humidity (non-condensing)	5 to 95%
Shock resistance	drop from 1,5 m onto concrete surface
Ingress protection	IP53
Maximal ambient light	100000lux
Others	

2 years

CODEWARE, s.r.o. Jaromírova 484/37

Warranty

120 00 Praha 2 - Nusle IČ: 61061395, DIČ: CZ61061395





