CODEWARE
no more searching

Honeywell

Dolphin CT60 - 2D, Android 7, WWAN, WLAN, NFC, Camera

The rugged Dolphin™ CT60 is ideal for enterprises requiring anywhere, anytime connectivity and fast data capture for maximum uptime and productivity. CT60 corresponds to the new Tobacco Directive - reads DotCode.

Honeywel Dolphin CT60 includes features that keep workers connected and productive throughout the day. Advanced industry-leading network connectivity facilitates large file transfers, video streaming and fast remote access to enterprise applications with enough power to last for the entire shift. Fast and accurate scanning of 1D and 2D codes and data capture is possible on most damaged or poorly printed codes. As an Android™ Enterprise Recommended device you'll have support for multiple versions of the Android OS. This lets you manage enterprise mobility with less cost and less risk than in the past.



Key featured:

- Mobility Edge Platform
- Android Enterprise Recommended
- Industry-Leading Future-Proof Protection
- Optimal Power and Connectivity
- Unparalleled Scanning Performance
- Rugged, Ergonomic Design
- DotCode



Technical Description

Functionality & Operation	
Wireless communication	Bluetooth®, NFC, WiFi, LTE
WLAN Features	IEEE 802.11 a/b/g/n/ac
CPU Type	Qualcomm Snapdragon 660 Octa-Core 2,2 GHz
Operating system	Android
Memory	3GB DDR4 RAM, 32 GB Flash
Display type	4.7" HD, 1280x720 px, LCD with backlight
Touch-screen panel	capacitive multi-touch
Expansion slot	Micro SD Card (SDHC) 512 GB
2D Code Symbologies	DotCode, all standard 2D-Codes
1D Barcode Symbologies	All standard one-dimension barcodes
Optical	
Camera	13 MPix , 4K video
Sensors	light sensor, proximity sensor, accelerometer, gyroscope, magnetometer , pressure sensor
Bar code scanner	2D Imager
Electrical	
Main battery pack	Li-Ion 4040 mAh, 3,6V
Mechanical	
Dimensions	Width: 82.5mm, Height: 160mm Length: 19mm
Weight	350g
Environment	
Operating temperature	-20 to 50°C
Storage temperature	-30 to 70°C
Operating humidity (non-condensing)	0 to 95%
Shock resistance	multiply drops from 2,4 m onto concrete surface, 1000 tumbles at 1 m
Electrical static discharge	±15kV air, ±8kV contact
Ingress protection	IP67



CODEWARE, s.r.o.
Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
https://www.codeware.cz/