

Honeywell®

Honeywell Robust mobile terminal ScanPal EDA51 - Android, GMS, WWAN, NFC, USB KIT

The ScanPal EDA51 mobile computer features the perfect combination of integrated scanning, powerful processing, intuitive touchscreen interface, and robust connectivity in a rugged, slim ergonomic design. It's ideal for small to medium-sized businesses to increase productivity in light duty retail, DSD, pickup and delivery, and field service applications. EDA 51 corresponds to the new Tobacco Directive - reads DotCode.

Key features:



- OS Android
- built with a snappy Qualcomm® Snapdragon™ 450 octa-core processor for fast data processing
- large 5 "touchscreen with 1280 x 720 HD resolution
- a powerful scanner for capturing damaged barcodes Honeywell N6603 engine
- 13MP camera with autofocus
- high capacity 4000mAh battery ensures long terminal life
- backward compatible with ScanPal EDA50 accessories, batteries, and chargers
- IP 64 sealing



Technical Description

| Functionality & Operation | |
|-------------------------------------|---|
| Indicators | Battery Status Indicator red/green/blue |
| Communication interface | Micro USB 2.0 |
| 1D Barcode Symbologies | All standard one-dimension barcodes |
| Memory | 2GB RAM 16 GB Flash |
| CPU Type | Qualcomm Snapdragon SDM450, 1.8 GHz octa-core |
| 2D Code Symbologies | all standard 2D-Codes, DotCode |
| Display type | 5" HD 1280x720px,with backlight |
| Operating system | Android |
| Wireless communication | Bluetooth®, GPS, LTE, NFC reader, WiFi |
| Expansion slot | Micro SD Card (SDHC) 128 GB |
| Touch-screen panel | capacitive multi-touch |
| WLAN Features | IEEE 802.11 a/b/g/n/ac |
| Optical | |
| Sensors | Accelerometer, light sensor, proximity sensor |
| Camera | 13 MPix |
| Electrical | |
| Main battery pack | Rechargeable Li-Ion battery 4000 mAh, 3,8V |
| Mechanical | |
| Dimensions | Width: 78.2mm, Height: 157mm, Length: 16.9mm |
| Weight | 272g |
| Environment | |
| Operating temperature | -10 to 50°C |
| Storage temperature | -20 to 70°C |
| Shock resistance | multiply drops from 1,2 m onto concrete surface, 300 tumbles at 0,5 m |
| Operating humidity (non-condensing) | 10 to 90% |
| Ingress protection | IP64 |

CODEWARE, s.r.o.
Jaromirova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
+420 737 274 952
codeware@codeware.cz
<https://eshop.codeware.cz/>

