



Honeywell®

Stratos 2422 Scanner Only, 353mm, Diamonex Platter

Honeywell's Stratos® 2400 5-sided, 360°-bioptic scanner increases productivity in demanding, high-volume seated environments where shorter vertical towers are required, and poor quality and highdensity bar codes are prevalent. Independent scanning planes and a modular design lower maintenance costs and ensure continuous operation.

The Honeywell Stratos 2421 offer pre-aligned optical scanning modules, and independent scanning planes which enable the scanner to maximize uptime and maintain productivity.



The scanner maximizes return on investment with analytical tools.

Stratos tools:

- **StratosSYNCTM Independent Scanning Planes:** Maintains productivity and uptime via independent scanning planes
- **StratosSCHOOL Operator Training Software:** Improves productivity and promotes safer scanning techniques
- **StratosSWAPTM Pre-Aligned Optical Scanning Modules:** Minimizes downtime and lowers the cost of service via modular optical scan engines
- **StratosSTATS Productivity Analytical Software:** Provides data critical to maintaining checkout productivity
- **Remote MasterMindTM Scanner Management Software:** Offers a quick and convenient solution for IT administrators seeking to manage all scanners within their network from a single remote location



Technical Description

Functionality & Operation

| | |
|-------------------------|--|
| Communication interface | RS232 |
| 1D Barcode Symbologies | All standard one-dimension barcodes, GS1-DataBar |

Optical

| | |
|-------------------------|--|
| Depth of scan field | H: 0 mm - 100 mm, V: 0 mm - 216 mm - 0,33 mm (13 mil) bar code |
| Minimum symbol contrast | 35% |
| Resolution | 4,5 mil (0,114 mm) |
| Scanning rate | 5400 scans/sec |
| Scannig pattern | 54 lines (38 lines horizontal, 16 lines vertical) |
| Bar code scanner | Laser |
| Light source | visible laser diode VLD 650 nm |

Mechanical

| | |
|------------|---|
| Dimensions | Width: 292mm, Height: 130mm Length: 353mm |
|------------|---|

Environment

| | |
|-------------------------------------|-------------|
| Operating temperature | 0 to 40°C |
| Operating humidity (non-condensing) | 5 to 95°C |
| Storage temperature | -40 to 60°C |

CODEWARE, s.r.o.

Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
<https://www.codeware.cz/>

