



## R120 Speedway Revolution, RFID reader UHF Gen2, 1 port

The Speedway Revolution UHF RFID reader delivers the performance, quality, and reliability necessary for maximum visibility of tagged inventory and assets. Impinj's innovative Speedway® Revolution RFID reader with Autopilot automatically optimizes its operation to the environment—delivering peak performance at all times.

With the Speedway Revolution's Autopilot, innovative firmware features work together, automatically optimizing the reader operation to its environment—delivering peak performance at all times.



- **Autoset** continuously optimizes the reader's configuration for the best, most reliable performance. The Speedway Revolution senses levels of RF noise and interference, automatically selecting the appropriate settings.
- **Low duty cycle** reduces RF interference, power consumption, and energy costs. The Speedway Revolution only transmits when tags are in the field, helping to clear the air of unnecessary RF noise.
- **Dynamic antenna switching** improves throughput and helps the reader work more efficiently. Speedway Revolution senses where tags are in the field and automatically focuses more time on the antennas with the largest tag populations in view.

### Key features:

- Autopilot (automatically senses environment and configures settings for best performance)
- 1, 2 and 4 antenna port configurations
- Power over Ethernet (PoE) and cellular modem connectivity
- Industry standard application interface with support for EPCglobal Low Level Reader Protocol (LLRP)
- Quality design resulting in industry's highest reliability
- Global partner and support network





# Technical Description

## Functionality & Operation

Antennas, Antenna inputs	1 mono-static port
Communication interface	USB Ports: 1 device (Type B), 1 host (Type A), 10/100BASE-T Ethernet
Maximal transmit power	30dBm
Network services	DHCP , Static or Link Local Addressing (LLA) with Multicast DNS (mDNS)
RFID transponder protocols	ISO 18000-63 GS1/EPCglobal UHF Gen2
Frequency	UHF: 865 - 930 MHz

## Electrical

Power Source	+24 VDC @ 800mA
--------------	-----------------

## Mechanical

Dimensions	Width: 190mm, Height: 30mm Length: 175mm
Weight	771g

## Environment

Relative humidity (non-condensing)	5 to 95%
Operating temperature	-20 to 50°C
Ingress protection	IP52
Vibrations resistance	MIL-STD-810G

## Others

Development tools	Speedway SDK, ETK and LTK library support
Application software	Impinj Web Management UI, Impijn RShell Management Console, SNMPv2 MIBII, EPCglobal Reader Management, Syslog

### CODEWARE, s.r.o.

Jaromírova 484/37  
120 00 Praha 2 - Nusle  
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444  
codeware@codeware.cz  
<https://www.codeware.cz/>

