ZEBRA

MC9300 Mobile Computer, 2D Standard Range (SE4770), IST, Wi-Fi, BT, 29 keys, handle, Android

The ultimate ultra-rugged Zebra MC9300 — the next evolution of the world's best-selling and most trusted Android enterprise mobile computer. Your workers get the ultimate in simplicity with Android, an operating system your workers already know well, a larger advanced touch display and more. Handle all of your applications with the ultimate in processing power and memory, plus new data capture capabilities that include optional front and back cameras, extraordinary scan ranges The new battery runs twice as long as the MC9200 on a single charge. Get the ultimate in workforce productivity and operational efficiency in your organization with the ultra-rugged MC9300.

The MC9300 terminal is designed for the most demanding environments. It is practically waterproof, resistant to dust, shocks and falls from a height of up to 2.4 m. The Corning Gorilla Glass display ensures resistance to scratches and impacts. Whether you work in the cold, frost or in the presence of hazardous materials, the terminal can handle almost any of your requirements.

Key features:

- The large multi-touch 4.3 in. WVGA with Corning Gorilla Glass
- ultra-rugged construction
- Program LifeGuard
- PowerPrecision+ battery technology
- Zebra Mobility DNA

Technical Description

Functionality & Operation

Keyboard	29 keys, numeric
Wireless communication	Bluetooth®, WiFi
Touch-screen panel	capacitive multi-touch
Communication interface	USB
Operating system	Android
Memory	
Expansion slot	MicroSD 32GB SDHC, 256GB SDXC
CPU Type	Qualcomm Snapdragon 660 octa-core, 2.2 GHz
Display type	4,3" WVGA color display, 800x480, Corning Gorilla Glass, LED backlight
WLAN Features	IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/w
WPAN Features	Bluetooth V5.0 Class 2, with BR/EDR, BLE Support
Audio	built-in microphone and speaker . PTT voice, Bluetooth Headset

Optical

Bar code scanner	2D Imager Standard Range SE4770
Sensors	accelerometer, light sensor , IST - Interactive Sensor

Electrical

Main battery pack	Li-Ion 7000mAh, 3,6V

Mechanical

Dimensions	Width: 88mm, Height: 240mm Length: 189mm
Weight	765g

Environment

Electrical static discharge	±15kV air, ±8kV contact
Shock resistance	multiply drops from 2,4 m onto concrete surface 4000 tumbles at 1m
Operating temperature	-20 to 50°C
Operating humidity (non-condensing)	5 to 95%
Ingress protection	IP67
Storage temperature	-40 to 70°C