



# Honeywell®

## MK-7120 Orbit, USB, black

Orbit is an aggressive, omnidirectional presentation laser bar code scanner. Lightweight and rugged, Orbit is small in size but big in performance. Designed for applications where counter space is at a premium, Orbit is the ideal presentation scanner for retail, convenience, liquor and specialty stores. In addition, Orbit's unique, contoured shape allows it to be picked up and used as a hand-held when scanning large or bulky items.

Engineered with a large, easy-to-find sweet spot, the Orbit increases the first pass read rate for maximum productivity. The scanning head can be tilted vertically up to 30° for added flexibility when scanning various objects. Orbit has a patented 20-line omnidirectional scan pattern that produces 1,200 scan lines per second. These features increase the scanning through-put, without increasing the Orbit's size. The Orbit is engineered for easy configuration and utilizes user-replaceable cables, in order to meet the multiple application needs across the many markets it serves. Data editing or "parsing" is also a standard feature. Parsing enables the encoded information to be manipulated to meet the host system's requirements.



# Technical Description

## Functionality & Operation

|                          |                                                                                                                                 |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| 1D Barcode Symbolologies | Codabar, Code 128, Code 39, Code 93, EAN 13/UPCA, French Pharma Code, Industrial 2 of 5, Interleaved 2 of 5, Matrix 2 of 5, MSI |
| Communication interface  | USB, RS232, keyboard, IBM 46xx (RS485), OCIA, Laser Emulation, Light Pen Wand Emulation                                         |
| Configuration            | by programming barcodes                                                                                                         |
| Language support         | French, German, Italian, Norwegian, Portuguese, Swedish, US and UK English, Belgian                                             |

## Optical

|                         |                                                                   |
|-------------------------|-------------------------------------------------------------------|
| Scanning rate           | 1120 scan lines per second; single line: 56 scan lines per second |
| Scannig pattern         | 5 directions                                                      |
| Minimum symbol contrast | 35%                                                               |
| Maximal skew angle      | 60°                                                               |
| Depth of scan field     | 0-215 mm (13 mil barcode)                                         |

## Electrical

|                               |                   |
|-------------------------------|-------------------|
| Power Source                  | 5 VDC $\pm$ 0.25V |
| Power Consumption - Standby   | 850mW             |
| Power Consumption - Operation | 900mW             |

## Mechanical

|            |                                           |
|------------|-------------------------------------------|
| Dimensions | Width: 150mm, Height: 105mm Length: 102mm |
| Weight     | 400g                                      |

## Environment

|                                   |                                       |
|-----------------------------------|---------------------------------------|
| Operating temperature             | 0 to 40°C                             |
| Storage temperature               | -40 to 60°C                           |
| Storage humidity (non-condensing) | 5 to 95%                              |
| Shock resistance                  | drop from 1,2 m onto concrete surface |

## Others

|                |                                        |
|----------------|----------------------------------------|
| Certifications | BSMI, C-Tick, CE, FCC Class A, IC, MIC |
|----------------|----------------------------------------|

### CODEWARE, s.r.o.

Jaromírova 484/37  
120 00 Praha 2 - Nusle  
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444  
codeware@codeware.cz  
<https://www.codeware.cz/>

