



PC42t - thermal transfer printer, 203dpi, USB, RS232, LAN

Easy to install, friendly price and ease of use makes the printer Honeywell PC42t ideal companion when printing bar codes, especially in manufacturing, healthcare and logistics.

New, efficient and economical printer Honeywell PC42t with the possibility of printing on media up to a width of 110 mm Ribbon length up to 300 meters (saving up to 30% compared to the competition). This printer is suitable for printing in low volume applications.



Key features of the printer Honeywell PC42t:

- compact size
- ease of installation
- cost-friendly
- intuitive easy media loading
- 64 MB Flash Memory 64 MB SDRAM
- communication interfaces: USB, USB host, Ethernet and serial

Video: YOUTUBE='UYYNsgHzr4U'

Technical Description

| Functionality & Operation | |
|---------------------------|---|
| Print mode | direct thermal, thermal-transfer |
| Memory | 64MB Flash |
| Memory | 64MB DRAM |
| 2D Code Symbologies | all standard 2D-Codes |
| Maximal print width | 104mm |
| Operation interface | 1x button |
| Communication interface | USB |
| 1D Barcode Symbologies | All standard one-dimension barcodes |
| Commands set | TSPL-EZ |
| Print resolution | 203dpi |
| Print speed | 102mm/sec (4 ips) |
| Electrical | |
| Power Source | 100-240V, 50-60Hz |
| Mechanical | |
| Body housing | double-walled plastic |
| Color | black |
| Dimensions | Width: 226mm, Height: 177mm Length: 297mm |
| Weight | 2.5kg |
| Consumables | |
| Max. ribbon length | 300m |
| Ribbon core diameter | 12.7mm |
| Maximal paper width | 110mm |
| Maximal roll diameter | 127mm |
| Max. ribbon diameter | 68mm |
| Ribbon width | 25.4 to 109.2mm |
| Media core diameter | 25.4 to 38.1mm |
| Minimal paper width | 25.4mm |
| Minimal label length | 9.6mm |

CODEWARE, s.r.o. Jaromírova 484/37 120 00 Praha 2 - Nusle IČ: 61061395, DIČ: CZ61061395

+420 222 562 444 codeware@codeware.cz https://www.codeware.cz/



