

# Honeywell®

## Honeywell PC42t - thermal transfer printer, 203dpi, USB, RS232, LAN

Easy to install, friendly price and ease of use makes the printer Honeywell PC42t ideal companion when printing bar codes, especially in manufacturing, healthcare and logistics.

New, efficient and economical printer Honeywell PC42t with the possibility of printing on media up to a width of 110 mm Ribbon length up to 300 meters (saving up to 30% compared to the competition). This printer is suitable for printing in low volume applications.




### Key features of the printer Honeywell PC42t:

- compact size
- ease of installation
- cost-friendly
- intuitive easy media loading
- 64 MB Flash Memory 64 MB SDRAM
- communication interfaces: USB, USB host, Ethernet and serial

Video:

YOUTUBE='UYYNsgHzr4U'



# Technical Description

Functionality & Operation	
Communication interface	RS232, USB
1D Barcode Symbologies	All standard one-dimension barcodes
Print mode	direct thermal, thermal-transfer
Maximal print width	104mm
Print speed	102mm/sec(4 ips)
Print resolution	203dpi
Memory	64MB Flash, 64MB DRAM
Operation interface	1x button
2D Code Symbologies	all standard 2D-Codes
Commands set	TSPL-EZ
Electrical	
Power Source	100-240V, 50-60Hz
Mechanical	
Dimensions	Width: 226mm, Height: 177mm, Length: 297mm
Weight	2.5kg
Body housing	double-walled plastic
Color	black
Consumables	
Maximal paper width	110mm
Maximal roll diameter	127mm
Minimal paper width	25.4mm
Ribbon width	25.4 to 109.2mm
Max. ribbon diameter	68mm
Max. ribbon length	300m
Ribbon core diameter	12.7mm
Media core diameter	25.4 to 38.1mm
Minimal label length	9.6mm
Environment	

**CODEWARE, s.r.o.**  
Jaromirova 484/37  
120 00 Praha 2 - Nusle  
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444  
+420 737 274 952  
codeware@codeware.cz  
<https://eshop.codeware.cz/>

