



Birch PRP-003 Thermal Receipt Printer with autocutter, USB & WLAN, black, print in Czech

Quiet, fast and powerful - and yet cost very effective. This is thermal printer PRP-003. POS Printer PRP-003 has a large 4MB input memory buffer and faster interfaces: USB 2.0, in the case of network model the Ethernet of 10/100 Base-T specification. It is equipped with a jack to open cash drawer and automatic cutter.



Technical Description

Functionality & Operation

| | |
|-------------------------|--------------------------------------------------------------------------------------------------------|
| Communication interface | 802.11a/b/g/n, USB, RJ-11 cash drawer port (DC 24V/1A) |
| Print mode | direct thermal |
| Maximal print width | 80mm |
| Print speed | 220mm/sec(9 ips) |
| Print resolution | 203dpi |
| Inter-dot space | 0.125mm |
| Fonts | Font A: 1.5x3 mm(48 columns), Font B: 1.13x2.13 mm(64 columns), ASCII: 13 international character sets |
| Wireless communication | WiFi |
| Commands set | ESC/POS |
| WLAN Features | IEEE 802.11 b/g/n |

Electrical

| | |
|--------------|--------------|
| Power Source | +24 VDC/2.5A |
|--------------|--------------|

Mechanical

| | |
|------------|--------------------------------------------|
| Dimensions | Width: 200mm, Height: 145mm, Length: 145mm |
|------------|--------------------------------------------|

| | |
|--------|-----|
| Weight | 2kg |
|--------|-----|

Consumables

| | |
|---------------------|------|
| Maximal paper width | 80mm |
|---------------------|------|

| | |
|-----------------------|------|
| Maximal roll diameter | 80mm |
|-----------------------|------|

| | |
|-----------------|--------------------------|
| Paper thickness | 53 to 80g/m ² |
|-----------------|--------------------------|

Environment

| | |
|-----------------------|-----------|
| Operating temperature | 0 to 50°C |
|-----------------------|-----------|

| | |
|---------------------|-------------|
| Storage temperature | -20 to 60°C |
|---------------------|-------------|

| | |
|-----------------------------------|-----------|
| Storage humidity (non-condensing) | 10 to 90% |
|-----------------------------------|-----------|

| | |
|-------------------------------------|-----------|
| Operating humidity (non-condensing) | 10 to 80% |
|-------------------------------------|-----------|

CODEWARE, s.r.o.

Jaromirova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
+420 737 274 952
codeware@codeware.cz
<https://eshop.codeware.cz/>

