



RK95: Rugged mobile logistic and warehouse terminal, 2D imager, WIFI, GMS, IP65, 38 keys, HC battery, USB

The handheld computer RK95 is the successor of the Cipherlab 9700. The data processing is based on a 2.2 GHz octa-core processor. The application can use 4 GB of RAM and 64 GB of flash memory. Users can choose between a numeric (38-key) or alphanumeric (52-key) keypad. Hot-swap feature enables the discharged battery replacement during the work. The device has Android Enterprise Recommended (AER) certification.

The CipherLab RK95 is a device with Android operating system characterized by its robust design and simple data acquisition. A large 4.3-inch display can be operated according to the manufacturer with a finger, a glove and a pen. Even wetness is no problem.



Barcodes can be read with the handheld at distances from 7.6 cm up to 21.4 m (the 2X model), according to Cipherlab. On request, it can also be equipped with an NFC reading function. The device is resistant to water and dust and offers a high fall protection, according to the manufacturer. Special batteries could also be used at low temperatures down to -30 ° C. The keyboard should remain free of ice for up to seven hours under such conditions. If necessary, a temperature sensor in the unit controls the integrated heating.

Moreover, the RK95 comes with a hot-swap feature that the low battery can be simply replaced with a fully charged one even without leaving your current applications.

High security standards thanks to the Google certification

The CipherLab RK95 is certified for Google's GMS and it has also <u>Android Enterprise Recommended (AER) certification</u>. This gives high safety standards to a user. The manufacturer also guarantees 90-day safety updates over the first five years after purchase.



























Technical Description Functionality & Operation built-in microphone and speaker , PTT voice, Bluetooth headset $\,$ Audio Expansion slot SIM card Wireless communication LTE, NFC, WiFi, Bluetooth® Indicators 4x LED, vibrator, speaker **WLAN Features** IEEE 802.11 a/b/g/n/ac/e/d/h/i/r/k/v/w **WPAN Features** Bluetooth® Class 2 v5.0 BR/EDR, BLE Display type 4,3" WVGA color display, Corning Gorilla Glass Touch-screen panel capacitive multi-touch 802.11 a/b/g/n/ac/d/h/i/r/k/v/w dual band, Bluetooth 5.0 BR/EDR & BLE, WLAN (WiFi), WWAN, OTG, Communication interface keyboard, Audio, USB 1D Barcode Symbologies All standard one-dimension barcodes Operating system Android 9.0, Android Enterprise Recommended (AER) **CPU Type** Octa-core over 2.2 GHz 64GB Flash, 4GB RAM Memory Expansion slot Micro SD Card (SDXC) 32 GB, SDXC 2TB 2D Code Symbologies all standard 2D-Codes Bluetooth profiles GAP, SDP, HSP, SPP, GOEP, OPP, HFP, PAN, A2DP, AVRCP, GAVDP, HID, PBAP Optical Camera 13 MPix, with LED flash Sensors light sensor, proximity sensor, e-compass, gyroscope, motion sensor Electrical Main battery pack Extended: Li-Ion 6000 mAh, 3,7V Main battery pack operating time 8hr Mechanical **Body housing** ABS plastic with rubber Dimensions Width: 80mm, Height: 216mm Length: 30mm **Environment**

Storage temperature	-30 to 70°C
Operating temperature	-20 to 50°C
Storage humidity (non-condensing)	5 to 95%
Electrical static discharge	±15kV air, ±8kV contact
Shock resistance	1000 tumbles at 1 m, multiply drops from 1,8 m onto concrete surface
Ingress protection	IP65
Others	

FEC. DC CDDC CCC NCC DCMI CF WEFF DallC DFACIL For DIC WDC AFR (Andrew Heranging	Warranty	1 year
Certifications FCC, BC, SRRC, CCC, NCC, BSMI, CE, WEEE, ROHS, REACH, EFP, BIS, WPC, AER (Android Enterprise Recommended) , CA65	Certifications	FCC, BC, SRRC, CCC, NCC, BSMI, CE, WEEE, RoHS, REACH, ErP, BIS, WPC, AER (Android Enterprise Recommended) , CA65

Third Parti: SOTI MobiControl, Xamarin Binding, iVanti Velocity Terminal Emulator and Browser, AirWatch, Application software

Development tools

CipherLab API, Android 9 Standard API

Application software

CipherLab: ReMoCloud®, Wireless Mobile Deployment System(WMDS), Android Device Conguration(ADC), BarcodeToSetting, App-Lock,Button Assignment, Reader Conguration, Signature Capture, Airlock Browser, Mirror Terminal Emulator, Software trigger

CODEWARE, s.r.o. Jaromírova 484/37 120 00 Praha 2 - Nusle

120 00 Praha 2 - Nusle IČ: 61061395, DIČ: CZ61061395





