

ME340-E-LCD Metal Industrial Bar Code Printer, 300 dpi, 4 ips, LAN+USB

The TSC ME240 series of industrial thermal label printers was designed to offer the right features at the best value in the industry. The ME240 / ME340 features a small footprint and low profile design that fits where larger industrial printers do not. Its quiet operation and fast label throughput is equally at home, in the office or shop floor environment. The printers all-metal construction and die-cast aluminum print engine is durable enough to withstand the toughest production environments.

Standard features of the TSC ME240 / ME340 barcode printer include USB and Serial connectivity, a full featured control panel with LCD display, 3-buttons and 3-LED display, Real Time Clock, 8 MB DRAM memory, 4 MB FLASH memory and an SD



- Flash memory card slot that allows for FLASH memory expansion up to 4 GB. TSC printers have the Therm

al

Smart Control techn
ology, a patented elect
ro

atures TSPL-EZ firmware that is easy to set up and use. TSPL-EZ offers automatic TPLZ (Translation Printer Language Zebra®) and TPLE (Translation Printer Language Eltron®) language emulation right out of the box. The printer simply translates each label format as the printer receives it, without any previous manual switching of the currently used printing language. Key Features of the ME240 / ME340 Industrial Bar Code Printer 3-button 3-LED and LCD display control panel Easily adjustable sensors Smart Thermal Control technology significantly extends printhead life and ensures sharper print output Print head pressure adjustment knobs 450 meter ribbon capacity Flexible firmware structure allows the printer to emulate popular printer languages Available in 203 dpi and 300 dpi resolutions Up to 4 Gigabyte Flash memory expansion using SD Flash memory Fast label throughput Loading the media: YOUTUBE='WbixzrwUdOU'



Technical Description

Functionality & Operation	
Communication interface	Ethernet, USB, RS232
Print speed	102mm/sec (4 ips)
Print resolution	300dpi
Maximal print length	1016mm -152.4 mm (mode peeler)
Operation interface	ON/OFF, 7x button
Print mode	direct thermal, thermal-transfer
Maximal print width	104mm
Memory	8MB DRAM
Memory	4MB Flash
Fonts	8 alpha-numeric bitmap fonts
Fonts	CG Triumvirate Bold Condensed scalable font
1D Barcode Symbolologies	Codabar, Code 11, Code 128, Code 39, Code 93, EAN 13/UPCA, EAN 8, GS1 Data Bar (RSS), China Postal Code, Logmars, MSI, Plessey, Postnet
2D Code Symbolologies	Aztec, Data Matrix, MaxiCode, PDF417, QR code
Fonts & barcode rotation	0°, 90°, 180°, 270°
Commands set	TSPL-EZD, Intermec, SATO, Markpoint
Expansion slot	SD Card (SDHC)
Display type	LCD graphic, with backlight
Optical	
Sensors	open print-head detector, reflective, ribbon end sensor, transmissive
Resolution	128x64 px
Electrical	
Power Source	Input: 100 ~ 240 VAC, 50~60 Hz, 5A
Mechanical	
Dimensions	Width: 434mm, Height: 286mm Length: 259mm
Weight	11kg
Body housing	sheet metal
Consumables	
Maximal roll diameter	203mm
Max. ribbon length	450m
Max. ribbon diameter	81mm
Ribbon core diameter	25.4mm
Ribbon width	40 to 110mm
Media type	black-marked media, notch, continuous, fan-fold, perforated
Minimal paper width	25.4mm
Maximal paper width	118mm
Media thickness	0.06 to 0.28mm
Media core diameter	25.4 to 76.2mm

Minimal label length	5mm
Minimal label length	25.4mm (peeler mode)
Minimal label length	25.4mm (cutter mode)
Environment	
Operating temperature	5 to 40°C
Operating humidity (non-condensing)	25 to 85%
Storage temperature	-40 to 60°C
Storage humidity (non-condensing)	10 to 90%
Others	
Certifications	CCC, cUL, FCC Class A, RoHS, UL, WEEE, CE Class A, C-Tick Class A, TÜV/Safety
Optional accessories	cutter, dispenser kit, internal Ethernet interface, USB host, Centronics Parallel, Bluetooth, KP-200 Plus keyboard display unit, KU-007 Plus smart keyboard
Warranty	2 years (printer), 25000 m or 6 months (print head), 50000 m or 12 months (printing cylinder), approved material CODEWARE

CODEWARE, s.r.o.
 Jaromírova 484/37
 120 00 Praha 2 - Nusle
 IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
 codeware@codeware.cz
<https://www.codeware.cz/>

