

TSC TTP-225 Desktop Barcode Printer, TT, 203 dpi, 5 ips, LCD, LAN

Desktop Barcode Printer TSC- TTP 225 has all the qualities sought customers for small printers. It is lightweight, portable, quiet, durable and very favorable price. He also offers parameters that are projected for the middle class printers: print speed of up to 127 mm / s (5 ips) print resolution 203/300 DPI, easy media loading, price performance ratio and easy connection.

Company TSC is a longtime producer of the full range of barcode printers. One of them is a thermal transfer printer TSC TTP- 225. The offer still in version TTP 323 with higher print resolution. This printer offers the ideal combination of low prices, high print quality, long life and high reliability. Despite its small size offers high performance that customers have come to expect TSC printers. It is suitable for healthcare, retail, service stations or offices. It is fully compatible with the command sets Eltron and Zebra.



TSC printers have the Thermal Smart Control technology, a patented electronic print head temperature control. Print output is sharper because of that technology and, what's even more important, printhead life is several times longer.

Basic features of barcode printers TTP 225:

- thermal transfer printing - print speed of up to 127 mm / s - 5 ips - 203/300 DPI print resolution
- Smart Thermal Control technology significantly extends printhead life and ensures sharper print output - easy media loading - LCD display - Memory 4 MB Flash, 8MB SDRAM - interface - USB 2.0, RS 232 - high-quality housing material - up to 90 m long ribbon - SD expansion card Loading

the media: YOUTUBE



Technical Description

Functionality & Operation	
Communication interface	USB, RS232
1D Barcode Symbologies	All standard one-dimension barcodes
Print mode	thermal-transfer
Maximal print width	54mm
Print speed	127mm/sec(5 ips)
Print resolution	203dpi
Fonts	8 alpha-numeric bitmap fonts, Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font
Maximal print length	2286mm
Memory	4MB Flash, 8 MB SDRAM,microSD card reader for Flash memory expansion, up to 4 G
Operation interface	1x button
2D Code Symbologies	PDF417, MaxiCode, Data Matrix, QR code, Aztec
Commands set	TSPL-EZ
Fonts & barcode rotation	0°, 90°, 180°, 270°
Optical	
Sensors	open print-head detector, Ribbon end sensor, transmissive, reflective
Electrical	
Power Source	Input: AC 100-240V, 1A, 47-63HZ, Output: DC 24V, 2.08A, 50W
Mechanical	
Dimensions	Width: 140mm, Height: 177mm, Length: 241mm
Weight	2.45kg
Body housing	double-walled plastic
Color	white
Consumables	
Maximal paper width	60mm
Maximal roll diameter	127mm
Media type	black-marked media, continuous, fan-fold, notch, wristband, perforated
Minimal paper width	15mm
Ribbon width	56 to 58mm
Max. ribbon length	90m
Media thickness	0.06 to 0.19mm
Media core diameter	25.4 to 38mm
Environment	
Operating temperature	5 to 40°C
Storage temperature	-40 to 60°C
Storage humidity (non-condensing)	10 to 90%
Operating humidity (non-condensing)	25 to 85%
Others	

Certifications

FCC (Class B), CE Class B, C-Tick Class B, UL, cUL, CCC, TÜV/Safety

Warranty

2 years (printer), 25000 m or 6 months (print head), 50000 m or 12 months (printing cylinder), approved material CODEWARE

CODEWARE, s.r.o.
Jaromirova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
+420 737 274 952
codeware@codeware.cz
<https://eshop.codeware.cz/>

