

TTP-247 Desktop Barcode Printer, 203 dpi, 7 ips, USB+LPT+RS232

Based on the design of its best-selling predecessor, the TTP-245 Plus, the TTP-247 runs at an impressive 7 inches per second, printing up to 4 inches wide at 203 dpi resolution. A second model in the series – the TTP-345 – offers high resolution 300 dpi printing at 5 inches per second. Both models offer 8 MB of SDRAM and 4 MB of onboard Flash memory. Gigabytes of Flash memory can be added via an onboard SDHC card reader.

Like its predecessor, the TTP-247 series features a user-friendly clamshell design for easy drop-in media loading, along with a rugged double-wall design that is stronger and more durable than other thermal transfer mechanisms on the market. Its innovative two-motor gear-driven engine is powerful enough to handle a 300-meter-long ribbon and label rolls up to 8.4 inches in diameter when used external unwinder.



By using two motors instead of the usual one, TTP-247 series printers operate at lower torque, reducing noise, decreasing wear and tear, and extending printer life. The platform's user-friendly design makes it easy for operators to load and unload ribbons, and its 300-meter capacity is more than four times the industry-standard length for desktop printers.

TSC printers have the Thermal Smart Control technology, a patented electronic print head temperature control. Print output is sharper because of that technology and, what's even more important, printhead life is several times longer.

Key Features of TSC TTP-247 Bar Code Printer:

- Up to 177.8 mm (7") per sec. print speed
- 4 MB Flash memory and 8 MB SDRAM memory
- SD Flash memory expansion up to 4 GB
- User-friendly clamshell design
- Label gap sensor & full-range adjustable black mark sensor
- Parallel, serial & USB 2.0 interfaces
- Main board integrated with internal Ethernet (factory option)
- Label capacity up to 214 mm OD (8.4" OD)
- Ribbon capacity up to 300 m (984')
- TSPL-EZ™ firmware for plug-n-play ease
- Optional peel-off module, cutter module, stand-alone keyboard and scanner
- Smart Thermal Control technology significantly extends printhead life and ensures sharper print output



Technical Description

| | |
|-------------------------------------|--|
| Functionality & Operation | |
| Print resolution | 203dpi |
| Maximal print length | 2286mm |
| Maximal print width | 108mm |
| Print speed | 178mm/sec , 7 ips (peel-off max. 3 ips) |
| Memory | 8MB DRAM |
| Memory | 4MB Flash |
| Expansion slot | SD Card |
| Communication interface | USB, Parallel Centronics, RS232 |
| Operation interface | 2x button |
| Fonts | 8 alphanumeric bitmap fonts, 1 Monotype Imaging CG Triumvirate Bold Condensed scalable font, Monotype True-Type Font engine |
| 1D Barcode Symbolologies | Codabar, Code 11, Code 128, Code 39, Code 93, Code128UCC, EAN 13/UPCA + ADDON 2, EAN 13/UPCA + ADDON 5, EAN 8 + ADDON 2, EAN 8 + ADDON 5, GS1 Data Bar (RSS), Interleaved 2 of 5, MSI, Plessey, Postnet, UPCA + ADDON 2, UPCA + ADDON 5, UPCE + ADDON 2, UPCE + ADDON 5, RSS-Stacked |
| 2D Code Symbolologies | Aztec, Data Matrix, MaxiCode, PDF417, QR code |
| Fonts & barcode rotation | 0°, 90°, 180°, 270° |
| Commands set | TSPL-EZ |
| Print mode | direct thermal, thermal-transfer |
| Optical | |
| Sensors | open print-head detector, reflective, ribbon end sensor, transmissive |
| Electrical | |
| Power Source | Input: 100 ~ 240 VAC, 50~60 Hz, 5A |
| Mechanical | |
| Body housing | double-walled plastic |
| Dimensions | Width: 213mm, Height: 188mm Length: 314mm |
| Color | dark grey |
| Consumables | |
| Max. ribbon length | 300m |
| Ribbon core diameter | 25.4mm |
| Maximal roll diameter | 127mm |
| Media type | black-marked media, continuous, fan-fold, notch, perforated |
| Media thickness | 0.06 to 0.19mm |
| Maximal paper width | 112mm |
| Minimal paper width | 20mm |
| Media core diameter | 25.4 to 76.2mm |
| Minimal label length | 10mm |
| Environment | |
| Operating temperature | 5 to 40°C |
| Operating humidity (non-condensing) | 25 to 85% |

| | |
|-----------------------------------|--|
| Storage temperature | -40 to 60°C |
| Storage humidity (non-condensing) | 10 to 90% |
| Others | |
| Warranty | 2 years (printer), 25000 m or 12 months (print head), 50000 m or 12 months (printing cylinder), approved material CODEWARE |
| Certifications | C-Tick Class B, CCC, CE Class B, cUL, FCC (Class B), TÜV/Safety, UL |
| Optional accessories | Bluetooth, KP-200 Plus keyboard display unit, KU-007 Plus smart keyboard |

CODEWARE, s.r.o.
Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
<https://www.codeware.cz/>

