

## Z-3392BT Plus Wireless Bar-2D-QR Code Scanner w. Cradle, USB, black

With rugged, aesthetic form factor and supreme scanning performance, the wireless scanner of barcode, 2D code & QR code Z-3392BT is able to work at distance up to 100 meters from it's wireless access point.

Its gun type design and large trigger allow users to aim at target easily; the ergonomic outline creates comfort in holding even for long hours. Along with ZEBEX advance decoding technology, the scanner is easy in operation and efficient in work, designed to benefit workers in all business sectors.



### Product Highlights of the wireless Z-3392BT scanner

- Ergonomic, rugged design
- Durable housing with gun-type design
- Clear LED indication
- Smart battery charging design
- Flexible communication options



# Technical Description

Functionality & Operation	
Communication interface	USB, JPOS, OPOS
Signal coverage	100m
Indicators	LED (green-red-blue)
Indicators	programmable beeper
1D Barcode Symbolologies	Codabar, Code 11, Code 128, Code 32, Code 39, Code 93, EAN 128, EAN 13, EAN 13/UPCA, EAN 13/UPCA + ADDON 2, EAN 13/UPCA + ADDON 5, EAN 8, EAN 8 + ADDON 2, EAN 8 + ADDON 5, GS1 128, GS1-DataBar, China Postal Code, Industrial 2 of 5, Interleaved 2 of 5, ISBN/ISSN, Italy Pharma Code, Matrix 2 of 5, MSI, Plessey, Postcode, Standard 2 of 5, UPCA, UPCE, Telepen
2D Code Symbolologies	Australia Post, Aztec, Codablock F, Data Matrix, GS1 DataBar Composite Code, GS1 DataMatrix, MaxiCode, Micro QR Code, MicroPDF417, QR code, PDF417, PLANET, Postnet, Royal Post, Composite codes
Wireless communication	Bluetooth®
Optical	
Light source	visible red LED 617 nm
Depth of scan field	30 mm ~ 280 mm
Maximal skew angle	120°
Maximal pitch angle	90°
Minimum symbol contrast	30%
Light source	visible red LED 617 nm
Resolution	4 mil
Viewing angle	0 to 38.6°
Bar code scanner	2D Imager (1280 x 720 pixels)
Electrical	
Power Source	+5V ±10%
Main battery pack	Li-Ion 2500 mAh, 3,7V
Power Consumption - Standby	70mA
Power Consumption - Operation	700mA
Main battery pack operating time	8hod
Battery charging time	6hod
Mechanical	
Maximal rotation angle	360°
Body housing	ABS plastic
Color	black
Dimensions	Width: 66.6mm, Height: 160.1mm Length: 82.4mm
Weight	200g
Environment	
Maximal ambient light	100000lux
Shock resistance	multiply drops from 1,5 m onto concrete surface
Operating temperature	0 to 50°C
Relative humidity (non-condensing)	5 to 90%
Storage temperature	-20 to 60°C

## Others

### Certifications

IEC 62471 Exempt, FCC DOC, RoHS, CE, FCC Part 15C, BSMI, VCCI, NCC, EN 300 328, ARIB STD-T66

### Bundled Accessories

battery, Charging and Communication Cradle, quick start guide, USB cable, power cord, charging supply

#### **CODEWARE, s.r.o.**

Jaromírova 484/37  
120 00 Praha 2 - Nusle  
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444  
codeware@codeware.cz  
<https://www.codeware.cz/>

