

## Z-8082 2D Image On-Counter Scanner, USB

The Z-8082 on-counter scanner offers flexibility with 2D image reading. The imagine technology allows versatile functionality with both 1D and 2D barcodes that satisfy your needs on regular market labels and consumer 2D coupons. Z-8082 not only provides efficiency with its instant decoding performance, it offers the convenience of wide scan zone and full-directional moving objects capture ability. This powerful device is ready for all heavy-loading challenges in retails.

**Main features of the on-counter POS bar code scanner Zebex Z-8082**



- High speed and reliable performance on all common 1D and 2D codes
- Offer convenience by its full-directional motion tolerance function and wide scan zone
- Aux port available for secondary scanner
- EAS supported for extended function
- VESA 100 compatible to satisfied your mounting demands

YOUTUBE='EJS1QdiwjN8'



# Technical Description

## Functionality & Operation

Indicators	Beeper (Buzzer), LED (Blue/ Red)
Communication interface	RS232, USB, OPOS, JPOS
1D Barcode Symbolologies	Code 39, Codabar, Code 128, Code 32, Code 93, Code128UCC, Discrete 2 of 5, EAN 128, EAN 13, EAN 13/UPCA, EAN 13/UPCA + ADDON 2, EAN 13/UPCA + ADDON 5, EAN 8, EAN 8 + ADDON 2, EAN 8 + ADDON 5, EAN-UCC, GS1 128, GS1 Data Bar (RSS), GS1 DataBar Expanded, GS1 DataBar Limited, GS1-DataBar, Interleaved 2 of 5, ISBN/ISSN, MSI, Standard 2 of 5, RSS-Stacked, Industrial 2 of 5, ISBT-128, UCC/EAN-128, UCC/EAN-128 K-MART, UPC/EAN, UPC/EAN/JAN, UPCA + ADDON 2, UPCA + ADDON 5, UPCE + ADDON 2, UPCE + ADDON 5, UPCE, UPCA, UPC5, UPC2, Trioptic Code 39, Code 128 subset A.B.C., IATA Code, Matrix 2 of 5
2D Code Symbolologies	Aztec, Data Matrix, GS1 DataBar Composite Code, GS1 DataMatrix, GS1 QR Code, PDF417, QR code, RSS, Composite codes, MicroPDF417, Micro QR Code, MaxiCode

## Optical

Light source	visible red LED 617 nm
Resolution	1280H x 960V pixels (1.2M)
Depth of scan field	0 ~ 200 mm
Resolution	5 mil (Code 39)
Maximal skew angle	47°
Maximal pitch angle	36°
Minimum symbol contrast	30%

## Electrical

Power Source	9 VDC/1A
--------------	----------

## Mechanical

Dimensions	Width: 152.1mm, Height: 140mm Length: 85mm
Weight	510g

## Environment

Operating temperature	0 to 50°C
Storage temperature	-40 to 70°C
Relative humidity (non-condensing)	5 to 95%
Shock resistance	drop from 1 m onto concrete surface

## Others

Certifications	CE, BSMI, FCC DOC, VCCI, IEC 62471 Exempt
----------------	---

### CODEWARE, s.r.o.

Jaromírova 484/37  
120 00 Praha 2 - Nusle  
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444  
codeware@codeware.cz  
<https://www.codeware.cz/>

