



CS6080 pocket scanner, corded, 1D/2D and OCR, kit USB, black

Do you need a cordless scanner for inventory in the store aisles and a corded hands-free scanner at checkout? What if you didn't have to deploy different scanners for different tasks? Introducing the CS60 Series Companion Scanner, featuring a groundbreaking design that easily converts between corded and cordless operation, handheld and hands-free, as your needs change. As a cordless scanner, the CS60 is small enough to tuck in a pocket and offers the latest mobile technology including contactless charging. As a corded scanner, the CS60 offers compact scanning for the checkout counter, self-service kiosk and more.

Do you need a cordless companion scanner paired to a cradle or mobile device, a corded handheld or a hands-free presentation scanner connected to a checkout stand? With the CS60, you don't have to choose. Simply swap the battery and corded USB converter at any time to change between corded and cordless scanning. Add the optional presentation stand to a corded scanner to automatically switch between hands-free and handheld modes. This unparalleled versatility minimizes investment risk as it's easy to meet new workflow needs or redeploy CS60 scanners to a different application.



Key features:

- A high-resolution megapixel sensor and Zebra's exclusive PRZM Intelligent Imaging technology
- A second programmable button that can be used to instantly toggle between two host applications
- Easy to clean seamless construction, IP65 sealing
- Qi Inductive Charging
- Split-Second NFC Tap-to-Pair
- The fully charged battery delivers 18 hours of power
- Bluetooth version extended 330 ft./100 m range
- Unique DataCapture DNA industry-preferred management tools















Technical Description

Functionality & Operation

Functionality & Operation	
Wireless communication	NFC
1D Barcode Symbologies	Base 32, Codabar, Code 11, Code 39, Code 93, Code 128, GS1-DataBar, Interleaved 2 of 5, Korean 3 of 5, MSI, Plessey, UPC/EAN
Communication interface	USB
2D Code Symbologies	Aztec, Composite codes, Data Matrix, DotCode, HanXin Code, MaxiCode, PDF417, OCR-B, OCR-A, OCR, MicroPDF417, Postnet, TLC-39, Micro QR Code
Keyboard	Supports over 90 international keyboards
Indicators	Direct Decode Indicator, Good Decode LEDs, beeper(adjustable tone and volume)
Optical	
Bar code scanner	2D Imager
Light source	Aiming Pattern: circular 525nm true green LED, Illumination: warm white LED
Resolution	1280 x 960 pixels
Minimal PCS value	20%
Maximal skew angle	60%
Maximal pitch angle	60%
Depth of scan field	30 - 660 mm
Electrical	
Power Source	4.5 ~ 5.5VDC
Main battery pack	735 mAh Lithium Polymer battery
Main battery pack operating time	18 hours, 13000 scans
Mechanical	
Color	black
Weight	56g
Dimensions	Width: 23mm, Height: 109mm Length: 46mm
Environment	
Operating temperature	0 to 50°C
Storage temperature	-40 to 70°C
Operating humidity (non-condensing)	5 to 95%
Shock resistance	multiply drops from 1,5 m onto concrete surface, 250 tumbles at 0,5 m

CODEWARE, s.r.o. Jaromírova 484/37

120 00 Praha 2 - Nusle IČ: 61061395, DIČ: CZ61061395

+420 222 562 444 codeware@codeware.cz https://www.codeware.cz/



