



DS2208 barcode scanner, 1D/2D, black, USB kit

The DS2200 Series is an affordable 1D/2D imager that does not compromise performance or features for price. Users can choose the model that best fits their POS needs—the corded DS2208 or the cordless DS2278. The DS2200 Series offers affordability with the deployment, ease of use and management simplicity businesses require.

2D barcodes have made their way to your Point of Sale (POS), appearing on everything from the items your customers are purchasing to printed and electronic coupons and loyalty cards. Your 1D scanner can't capture the new 2D codes, leading to exceptions that slow down the check-out process and frustrate customers at that key last personal touchpoint in your store. But with the DS2200 Series, you can scan it all. You get an affordable 1D/2D imager that doesn't compromise performance or features for price. And you can choose the model that best fits your POS needs



t
he corded DS220



Technical Description

Functionality & Operation

Indicators	Direct Decode Indicator, Good Decode LEDs, Rear View LEDs, beeper
Keyboard	Supports over 90 international keyboards
Communication interface	RS232, USB
1D Barcode Symbolologies	Base 32, Code 128, Code 39, Code 93, Plessey, MSI, UPC/EAN, GS1-DataBar, Korean 3 of 5, Italy Pharma Code, Codabar
2D Code Symbolologies	Composite codes, MicroPDF, TLC-39, Micro QR Code, MaxiCode, Data Matrix, Aztec, QR code, HanXin Code

Optical

Depth of scan field	0 - 368 mm
Maximal skew angle	65%
Maximal pitch angle	65%
Minimal PCS value	15%
Resolution	640 x 480 pixels
Light source	Aiming Pattern: Linear 624nm Amber LED
Bar code scanner	2D Imager

Electrical

Power Source	4.5 to 5.5 VDC Host Powered; 4.5 to 5.5 VDC External Power Supply
--------------	---

Mechanical

Color	black
Dimensions	Width: 66mm, Height: 99mm Length: 165mm
Weight	161.6g

Environment

Electrical static discharge	±15kV air, ±8kV contact
Maximal ambient light	107600lux
Shock resistance	250 tumbles at 0,5 m, multiply drops from 1,5 m onto concrete surface
Operating temperature	0 to 50°C
Operating humidity (non-condensing)	5 to 95%
Ingress protection	IP52
Storage temperature	-40 to 70°C

CODEWARE, s.r.o.

Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
<https://www.codeware.cz/>

