GK420t Desktop Thermal Transfer Bar Code Printer, 203 DPI, USB+Serial+Parallel

The best-in-class enhanced GX430t/GX420t desktop printer offers the widest range of features. The GX430t/GX420t has a sleek and compact design, boasts the easiest ribbon loading system on the market, and supports a variety of applications and industries.

Features:



- Small dimensions and easy-of-use
- The printer comes standard with ZPL and EPL programming languages
- Print speed up to 152 mm / s
- Extensive accessories cutter, peel off, Bluetooth
- Serial and USB ports, an optional extension of internal ZebraNet PrintServer
- Possible variants of 203 dpi (model GX420t)
- The easiest ribbon loading system



Technical Description

Functionality & Operation	
Print resolution	203dpi
Print speed	127mm/sec (5 ips)
Print mode	thermal-transfer, direct thermal
1D Barcode Symbologies	All standard one-dimension barcodes
2D Code Symbologies	all standard 2D-Codes
Communication interface	Parallel Centronics, RS232, USB
Maximal print width	104mm
Maximal print length	991mm
Programmable features	EPL2, ZPL I/ZPL II programming languages
Optical	
Sensors	reflective, transmissive
Mechanical	
Dimensions	Width: 254mm, Height: 194mm Length: 191mm
Weight	2kg complete set - 4,1 kg
Consumables	
Ribbon width	33 to 110mm
Max. ribbon diameter	34mm
Max. ribbon length	74m , Ribbon wound ink side out
Ribbon core diameter	12mm
Maximal paper width	108mm
Maximal roll diameter	127mm
Media type	black-marked media, continuous, fan-fold, Roll-feed, tags, tickets, perforated
Minimal paper width	19mm
Environment	
Operating humidity (non-condensing)	10 to 90%
Operating temperature	5 to 41°C
Storage temperature	-40 to 60°C
Storage humidity (non-condensing)	5 to 95%



CODEWARE, s.r.o.
Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
https://www.codeware.cz/