



GK420t Desktop Thermal Transfer Bar Code Printer, 203 DPI, USB+Ethernet

The best-in-class enhanced GX430t/GX420t desktop printer offers the widest range of features. The GX430t/GX420t has a sleek and compact design, boasts the easiest ribbon loading system on the market, and supports a variety of applications and industries.

Features:



- Small dimensions and easy-of-use
- The printer comes standard with ZPL and EPL programming languages
- Print speed up to 152 mm / s
- Extensive accessories cutter, peel off, Bluetooth
- Serial and USB ports, an optional extension of internal ZebraNet PrintServer
- Possible variants of 203 dpi (model GX420t)
- The easiest ribbon loading system



Technical Description

Functionality & Operation

| | |
|--------------------------|--|
| Communication interface | Ethernet, USB |
| Print speed | 127mm/sec (5 ips) |
| Print mode | direct thermal, thermal-transfer |
| Print resolution | 203dpi |
| 1D Barcode Symbolologies | All standard one-dimension barcodes |
| 2D Code Symbolologies | all standard 2D-Codes |
| Maximal print width | 104mm |
| Maximal print length | 991mm |
| Programmable features | EPL2, ZPL I/ZPL II programming languages |

Optical

| | |
|---------|--------------------------|
| Sensors | reflective, transmissive |
|---------|--------------------------|

Mechanical

| | |
|------------|---|
| Dimensions | Width: 254mm, Height: 194mm Length: 191mm |
| Weight | 2kg complete set - 4,1 kg |

Consumables

| | |
|-----------------------|--|
| Ribbon width | 33 to 110mm |
| Max. ribbon length | 74m , Ribbon wound ink side out |
| Max. ribbon diameter | 34mm |
| Ribbon core diameter | 12mm |
| Maximal paper width | 108mm |
| Maximal roll diameter | 127mm |
| Media type | black-marked media, continuous, fan-fold, Roll-feed, tags, tickets, perforated |
| Minimal paper width | 19mm |

Environment

| | |
|-------------------------------------|-------------|
| Operating humidity (non-condensing) | 10 to 90% |
| Operating temperature | 5 to 41°C |
| Storage temperature | -40 to 60°C |
| Storage humidity (non-condensing) | 5 to 95% |

CODEWARE, s.r.o.

Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
<https://www.codeware.cz/>

