



Zebra LS-2208: Increased productivity, lower TCO. High performance scanning fast. Durable, future-proof construction. Proven quality you can trust.

Increased productivity, lower TCO The LS2208 handheld scanner from Zebra offers high performance scanning at a moderate price. From a retail point-of-sale and a backroom to a patient's bedside or a school book checkout, the LS2208 provides fast, reliable scanning in a durable, lightweight form factor, delivering enhanced productivity and efficiency while reducing your total cost of ownership (TCO). High performance scanning



e to maximize user comfort. Durable, future-proof construction The LS2208 is engineered for continuous, heavy use all day, every day and has been tested to withstand multiple 5 ft./1.5m drops onto concrete. The patented single board construction eliminates a common point of failure the interconnection between multiple boards, and the liquid polymer scan element delivers integral shock protection to further ensure reliable operation. The scratch-resistant tempered glass helps to preserve barcode scanning accuracy. The integrated multiple interfaces, the universal cable compatibility and the support for emerging symbologies provide the investment protection you need to help ensure that the scanner you buy today will work with the system you use tomorrow.



# Technical Description

## Functionality & Operation

Communication interface	USB
Indicators	beeper, Good Decode LEDs, Direct Decode Indicator
1D Barcode Symbolologies	Code 128, Code 39, Code 93, Code 11, MSI, Plessey, UPC/EAN, Interleaved 2 of 5, Korean 3 of 5, GS1-DataBar, Base 32

## Optical

Scanning rate	100 scans/sec
Minimal PCS value	20%
Bar code scanner	Laser
Light source	650 nm Lased Diode Class 2
Maximal skew angle	10%
Maximal pitch angle	65%
Depth of scan field	0 - 1095 mm

## Electrical

Power Source	4.5 ~ 5.5VDC
Power Consumption - Standby	90mA
Power Consumption - Operation	175mA

## Mechanical

Dimensions	Width: 85mm, Height: 46mm Length: 152mm
Weight	150g

## Environment

Storage temperature	-40 to 70°C
Maximal ambient light	86080lux
Ingress protection	IP30
Electrical static discharge	±15kV air, ±8kV contact
Shock resistance	500 tumbles at 0,5 m, multiply drops from 1,5 m onto concrete surface
Operating humidity (non-condensing)	5 to 95%
Operating temperature	0 to 50°C

## Others

Warranty	5 years
----------	---------

**CODEWARE, s.r.o.**  
Jaromírova 484/37  
120 00 Praha 2 - Nusle  
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444  
codeware@codeware.cz  
<https://www.codeware.cz/>

