



LS2208 barcode scanner, USB KIT, black

Zebra LS-2208: Increased productivity, lower TCO. High performance scanning fast. Durable, future-proof construction. Proven quality you can trust.

Increased productivity, lower TCO The LS2208 handheld scanner from Zebra offers high performance scanning at a moderate price. From a retail point-of-sale and a backroom to a patient's bedside or a school book checkout, the LS2208 provides fast, reliable scanning in a durable, lightweight form factor, delivering enhanced productivity and efficiency while reducing your total cost of ownership (TCO). High performance scanni



e to maximize user comfort. Durable, future-proof construction The LS2208 is engineered for continuous, heavy use all day, every day and has been tested to withstand multiple 5 ft./1.5m drops onto concrete. The patented single board construction eliminates a common point of failure the interconnection between multiple boards, and the liquid polymer scan element delivers integral shock protection to further ensure reliable operation. The scratch-resistant tempered glass helps to preserve barcode scanning accuracy. The integrated multiple interfaces, the universal cable compatibility and the support for emerging symbologies provide the investment protection you need to help ensure that the scanner you buy today will work with the system you use tomorrow.



Technical Description

Functionality & Operation

Communication interface USB

Indicators beeper, Good Decode LEDs, Direct Decode Indicator

1D Barcode Symbolologies Code 128, Code 39, Code 93, Code 11, MSI, Plessey, UPC/EAN, Interleaved 2 of 5, Korean 3 of 5, GS1-DataBar, Base 32

Optical

Scanning rate 100 scans/sec

Minimal PCS value 20%

Bar code scanner Laser

Light source 650 nm Lased Diode Class 2

Maximal skew angle 10%

Maximal pitch angle 65%

Depth of scan field 0 - 1095 mm

Electrical

Power Source 4.5 ~ 5.5VDC

Power Consumption - Standby 90mA

Power Consumption - Operation 175mA

Mechanical

Dimensions Width: 85mm, Height: 46mm Length: 152mm

Weight 150g

Environment

Storage temperature -40 to 70°C

Maximal ambient light 86080lux

Ingress protection IP30

Electrical static discharge ±15kV air, ±8kV contact

Shock resistance 500 tumbles at 0,5 m, multiply drops from 1,5 m onto concrete surface

Operating humidity (non-condensing) 5 to 95%

Operating temperature 0 to 50°C

Others

Warranty 5 years

CODEWARE, s.r.o.

Jaromírova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
codeware@codeware.cz
<https://www.codeware.cz/>

