# RFID label Silverline II blade M730, 60mm x 25mm, PET, 400 lbl/roll - price per roll

The next generation of Silverline RFID on-metal labels build upon the printing and encoding performance many have relied on, with new materials and the latest chip technology, regionally tuned to offer up to 3X longer read ranges on-metal and improved readability on non-metal surfaces. This powerful RFID label that can, in many cases, replace a hard RFID tag. Optimal for asset tagging, this little giant is sure to find a million industrial uses, works on just about any surface material you slap it on.

The Confidex Silverline family is designed and verified to work with the Zebra ZT410 RFID Silverline and ZT411 On Metal printer. Other Zebra printers are not recommended or supported.

Read range:
On metal up to 10 m / 33 ft
On plastic up to 5 m / 16 ft
On liquid up to 4 m / 13 f

Technical Description

Functionality & Operation

Memory	128bit
Type of chip	Impinj® M730
RFID transponder protocols	EPCGlobal Class1 Gen2 ISO 18000□6C passive UHF RFID transporder
Frequency	UHF: 865 - 868 MHz (EU)

Mechanical

Dimensions	Width: 60mm, Height: 25mm Length: 1.4mm
Weight	0.9g

Consumables

Core diameter	76mm

Environment

Ingress protection	IP68
Operating temperature	-35 to 85°C