# RFID label Silverline II classic M730, 100mm x 40mm, PET, 350 lbl/roll - price per roll

The next generation of Silverline RFID on-metal labels build upon the printing and encoding performance many have relied on, with new materials and the latest chip technology, regionally tuned to offer up to 3X longer read ranges on-metal and improved readability on non-metal surfaces. This powerful RFID label that can, in many cases, replace a hard RFID tag. Ideal for applications such as industrial logistics, asset tracking and work-in-process monitoring. The label can also be attached on curved surfaces like liquid bottles and metallic cylinders without affecting its performance.

The Confidex Silverline family is designed and verified to work with the Zebra ZT410 RFID Silverline and ZT411 On Metal printer. Other Zebra printers are not recommended or supported.

Read range:
On metal up to 15 m / 50 ft
On plastic up to 9 m / 30 ft
On liquid up to 10 m / 33 ft

Technical Description

Functionality & Operation

Type of chip	Impinj® M730
Memory	128bit
RFID transponder protocols	EPCGlobal Class1 Gen2 ISO 18000□6C passive UHF RFID transporder
Frequency	UHF: 865 - 868 MHz (EU)

Mechanical

Weight	2.2g
Dimensions	Width: 100mm, Height: 40mm Length: 1.3mm

Consumables

Core diameter	76mm

Environment

Ingress protection	IP68
Operating temperature	-35 to 85°C