

Zebra ZT230 - 203 DPI, USB+RS232+LAN

The ZT200 series has been designed for ease of use, versatility and outstanding value. ZT230: Rugged all-metal case for long-lasting use; 450m ribbon capacity for increased uptime and fewer ribbon changes. ZT220: Durable high-impact polymer case for long-lasting use; 300m ribbon capacity; Simple single-use three-button user interface.

Space-saving design • Compact footprint and streamlined design fits easily in confined areas where space is at a premium • Elegant space-saving design with unique bi-fold door (requires 102mm/4" of opening space) fits easily into tight spaces, maximising work space Fast installation and integration • Ideal replacement printer for older Stripe and S4M models • Multiple connectivity options: parallel, 10/100 Ethernet, 802.11b/g/n wireless • Icon-based status LEDs provide immediate and easily visible printer status Intuitive, effortless media loading • Side-loading design eliminates complicated threading of supplies • Colour-coded cues give even first-time users visual guidance for loading ribbon and media • Illuminated moveable sensor is visible through the media for trouble-free sensor-position adjustment Print quality • Engineered for greater print precision with finetuned adjustments • Crisp, clean text and barcodes – even on narrow media Zebra reliability and durability • Built for light industrial and commercial environments • Energy Star®-compliant • Drive system designed for optimal performance, with minimal maintenance required Simplified serviceability • Easy, tool-less platen and printhead removal enable simple cleaning and replacement • Simple interchangeable connectivity options enable rapid printer changes and upgrade • Only three common tools needed for basic service



Technical Description

Functionality & Operation

1D Barcode Symbologies All standard one-dimension barcodes

Print mode direct thermal, thermal-transfer

Maximal print width 104mm

Print speed 152mm/sec(6 ips)

Print resolution 203dpi, 300dpi, optional

Maximal print length 3988mm(203 dpi), 1854mm(300 dpi)

Memory 128MB Flash

2D Code Symbologies all standard 2D-Codes

Consumables

Maximal paper width 114mm

Maximal roll diameter 203mm, 152mm

Media type black-marked media, paper and thermal-paper labels, tags

Minimal paper width 19mm

Ribbon width 40 to 110mm

Max. ribbon diameter 81mm(ZT230)

Max. ribbon length 450m

Media thickness 0.076 to 0.25mm

Environment

Operating temperature 5 to 40°C

Storage temperature -40 to 60°C

Storage humidity (non-condensing) 5 to 85%

Operating humidity (non-condensing) 20 to 85%

Others

Certifications VCCI, ICES-003 Class B, IEC 60950-1, UL, C-Tick, CCC, CE, FCC (Class B)

Warranty 1 years

CODEWARE, s.r.o.
Jaromirova 484/37
120 00 Praha 2 - Nusle
IČ: 61061395, DIČ: CZ61061395

+420 222 562 444
+420 737 274 952
codeware@codeware.cz
<https://eshop.codeware.cz/>

