



## ZXP3 - printer for printing plastic cards, two-sided printing, USB, LAN

The printer of plastic cards ZEBRA ZXP3 prints ZRaster method. It provides unparalleled quality print photo quality while ensuring the durability and life of the printing plastic cards. Printers also don't have a problem with print cards with contact chip or magnetic stripe that can also encode during printing.

Compact, easy to use and affordable sided Printer series ZXP3 using technology of direct printing on plastic cards. The printer to be installed on modules for encoding smart cards or modules, enabling the printer to connect to internal sítě. Tiskárna ZXP3 was mainly designed for occasional printing ID cards at less cost (about 2,500 cards per year). The printer has a very compact footprint, offers improved print quality in its class and an impressive print speed of 180 cards per hour. Zebra printer ZXP3 is a compromise between performance and cost. The ZXP Series 3 requires little technical support or user training. The quick-replace Load-N-Go™ smart ribbons have the added benefit of being eco-friendly, using less plastic and more biodegradable material than many competing brands. Print Touch™ uses Near Field Communication (NFC) to instantly retrieve helpful information about the ZXP Series 1 from any NFC-enabled smart device.



## Ideal for These Applicatio

ns

• Retail & Hospita lity • Identification & A ccess • Government & Edu

ca**tion Key** 

Fe

atures: • Dye-sublimation thermal transfer direc t to card • Two-sided full color or monochr ome printing • Edge-to-edge printing on standar d CR-80 media • Eco-Friendly Load-N-Go drop-in ribb on cartridges • Auto calibr ation of ribbon • ENERG Y STAR Certified • 100 card covered feed er (30mil-0,76mm) • 45 card capacity output hop per (30mil-0,76mm) • Magnetic strip e encoder: ISO 7811 • Frequ

ency range: 47-63Hz. • Zebra ix Series™ intelligent technology automatically detects and

authenticates ribbon • Card Size: CR-80, ISO

78









## **Technical Description**

## Functionality & Operation

rancaonancy & operation	
Communication interface	Ethernet, USB
Memory	32MB
Print speed	180 /cards/hour
1D Barcode Symbologies	Code 39, Code 128, EAN 8, EAN 13/UPCA
2D Code Symbologies	PDF417
Print resolution	300dpi
Electrical	
Power Source	100-240V, 50-60Hz
Mechanical	
Color	black
Dimensions	Width: 236mm, Height: 201mm Length: 368mm
Weight	5.5kg
Consumables	
Media thickness	0 to 0.762mm
Environment	
Operating temperature	15 to 30°C
Operating humidity (non-condensing)	20 to 65%
Storage temperature	-5 to 70°C
Storage humidity (non-condensing)	20 to 70%

CODEWARE, s.r.o. Jaromírova 484/37

120 00 Praha 2 - Nusle IČ: 61061395, DIČ: CZ61061395





